



AUTENTICO® Sealer

Product Description:

Autentico Sealer® is a high quality coating designed to protect walls and furniture painted with Autentico® Velvet and Venice.

Water resistant, low in VOC and water based, this coating is a perfect solution for surfaces which require extra defence such as kitchens, bathroom walls and applicable furniture. Autentico® Sealer dries with a matt finish allowing Autentico Paint's beautiful depth of colour to be revealed.

Location:

Interior.

Suggested Applications:

Can be applied to plaster, plasterboard, wood, masonry, PVC, metal and a wide range of other surfaces that have been prepared.

Preparation:

Autentico® sealer should be applied only when the painted substrate is fully dry, clean and stable. If applying over a painted wooden surface, it is recommended to apply a coat of Autentico Primer before painting to reduce the risk of bleed through.

Application:

Stir well prior to use. Apply two thin coats with brush or medium roller. (Thick coats will leave white patches). Autentico® Sealer will appear white in the tin but will dry transparent. The first coat must be diluted with 20% water and the second coat with 10-20% water.

It is possible to add Autentico Paint (max 5%) to Autentico® Sealer, this must be done in a third coat and should also be diluted with 10% water.

Drying Times:

Touch dry in 1 hour. Allow minimum of 2-hour drying time between coats. (Drying times may vary dependent on temperature, surface profile and porosity).

Coverage Rates:

Covers approximately between 8-13 m² per litre dependent on surface profile and porosity.

Packaging:

Autentico® Sealer is available in 100ml and 1 litre.

Limitations:

All Autentico products should not be applied in high humidity, below 10°C or above 30°C.

Storage:

Keep in a cool dry place. Away from risk of frost.

Cleaning and Disposal:

Remove excess paint from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Environmental Information:

This product contains less than 15 g/L VOC. EU target level for this product: 30g/L

Autentico® Pure and Natural Paints uses only the finest quality, low odour and minimal environmental impact raw materials. Our manufacturing processes are zero waste and all paint formulations are designed for maximum performance with minimum impact on user health.

Health and Safety:

Avoid contact with eyes, if contact occurs rinse well immediately with water. Safety data sheet available upon request.

Manufacturers Details:

Unit 4, The Glenmore Centre
Moat Way
Ashford
Kent
TN24 0TL

01233878303

www.autentico-paint.com
enquiries@autentico-paint.com