

Safety Data Sheet dated 31/5/2017, version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Mixture identification: Trade name: VELATURE Trade code: 383 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: Coating material 1.3. Details of the supplier of the safety data sheet Company: COLORIFICIO SAN MARCO S.P.A. Via Alta 10 30020 MARCON (VE) - Italy -Tel.+39 041 4569322 Fax. +39 041 5950153 Competent person responsible for the safety data sheet: sicurezza.prodotti@sanmarcogroup.it 1.4. Emergency telephone number Technical information: COLORIFICIO SAN MARCO SPA +39 041 4569322 (Monday - Friday 9.00-12.30; 13.30-17.00) **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP) Aquatic Chronic 3, Harmful to aquatic life with long lasting effects. Adverse physicochemical, human health and environmental effects: No other hazards 2.2. Label elements Hazard pictograms: None Hazard statements: H412 Harmful to aquatic life with long lasting effects. Precautionary statements: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents / container in accordance with national regulations. **Special Provisions:** EUH208 Contains reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Special provisions according to Annex XVII of REACH and subsequent amendments: None 2.3. Other hazards vPvB Substances: None - PBT Substances: None Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

383/8 Page n. 1 of 9



3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 1% - < 3%	2-butoxyethanol	Index number: CAS: EC: REACH No.:	111-76-2 203-905-0	 3.3/2 Eye Irrit. 2 H319 3.2/2 Skin Irrit. 2 H315 3.1/4/Oral Acute Tox. 4 H302 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332
>= 0. 0015% - < 0.005%	pyrithione zinc	CAS: EC: REACH No.:	13463-41-7 236-671-3 01- 2119511196 -46-XXXX	 3.1/3/Oral Acute Tox. 3 H301 4.1/C1 Aquatic Chronic 1 H410 M=10. 3.3/1 Eye Dam. 1 H318 4.1/A1 Aquatic Acute 1 H400 M=100. 3.1/4/Inhal Acute Tox. 4 H332
>= 0. 0015% - < 0.005%	terbutryn	CAS: EC:	886-50-0 212-950-5	 4.1/A1 Aquatic Acute 1 H400 M=100. 4.1/C1 Aquatic Chronic 1 H410 M=100. 3.1/4/Oral Acute Tox. 4 H302 3.4.2/1B Skin Sens. 1B H317
>= 0. 00015% - < 0. 0015%	reaction mass of 5- chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	Index number: CAS: EC:	613-167-00-5 55965-84-9 611-341-5	 3.2/1B Skin Corr. 1B H314 3.4.2/1A Skin Sens. 1A H317 4.1/A1 Aquatic Acute 1 H400 M=100. 4.1/C1 Aquatic Chronic 1 H410 M=10. 3.1/3/Oral Acute Tox. 3 H301 3.1/3/Dermal Acute Tox. 3 H311 3.1/1/Inhal Acute Tox. 1 H330

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed Treatment: None



SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media: Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

- None in particular.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove persons to safety. See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 Retain contaminated washing water and dispose it.
 In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
- Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Avoid contact with skin and eyes, inhaltion of vapours and mists.
- Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
- Keep away from food, drink and feed. Incompatible materials: None in particular. Instructions as regards storage premises: Adequately ventilated premises. 7.3. Specific end use(s)
 - None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
 - 2-butoxyethanol CAS: 111-76-2
 - OEL Type: EU TWA(8h): 98 mg/m3, 20 ppm STEL: 246 mg/m3, 50 ppm Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

383/8 Page n. 3 of 9



	xposure Limit Values
Z-1	butoxyethanol - CAS: 111-76-2 Worker Professional: 89 mg/kg - Consumer: 89 mg/kg - Exposure: Human Dermal -
	Frequency: Short Term, systemic effects
	Worker Professional: 1091 mg/m3 - Consumer: 426 mg/m3 - Exposure: Human
	Inhalation - Frequency: Short Term, systemic effects
	Worker Professional: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
	Worker Professional: 98 mg/m3 - Consumer: 59 mg/m3 - Exposure: Human Inhalatic Frequency: Long Term, systemic effects
	Consumer: 26.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
	Worker Professional: 246 mg/m3 - Consumer: 147 mg/m3 - Exposure: Human Inhala - Frequency: Short Term, local effects
	Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic eff
	xposure Limit Values
2-	butoxyethanol - CAS: 111-76-2
	Target: Fresh Water - Value: 8.8 mg/l
	Target: Marine water - Value: 0.88 mg/l
	Target: Freshwater sediments - Value: 34.6 mg/kg Target: Marine water sediments - Value: 3.46 mg/kg
	Target: Microorganisms in sewage treatments - Value: 463 mg/l
	Target: Food chain - Value: 20 mg/kg
	Target: Soil (agricultural) - Value: 2.33 mg/kg
82 Evo	osure controls
Eye prote	
	ot needed for normal use. Anyway, operate according good working practices.
	on for skin:
	o special precaution must be adopted for normal use.
	on for hands:
	ot needed for normal use.
	ory protection:
	ot needed for normal use.
	Hazards:
	DNe
Environn	nental exposure controls:
	bne
	ate engineering controls: one

9.1. Informa	tion on basic	physical and	chemical	pro
				-

in official official and	a onionniour proportio	0
Appearance:	liquid	
Colour:	various	
Odour:	characteristic	
Odour threshold:	N.A.	
pH:	N.A.	
Melting point / freezing point:	N.A.	
Initial boiling point and boiling r	ange: N.A.	
Solid/gas flammability:	N.A.	
Upper/lower flammability or exp	plosive limits:	N.A.
Vapour density:	N.A.	
Flash point:	N.A.	
Evaporation rate:	N.A.	
Vapour pressure:	N.A.	
Relative density:	1.09 kg/l	

383/8 Page n. 4 of 9



Solubility in oil: Partition coefficient (n-octanol	N.A.	N.A.
Auto-ignition temperature:	N.A.	N.A.
Decomposition temperature:	N.A.	
Viscosity:	N.A.	
Explosive properties:	N.A.	
Oxidizing properties:	N.A.	
9.2. Other information		
Miscibility:	N.A.	
Fat Solubility:	N.A.	
Conductivity:	N.A.	
Substance Groups relevant p	roperties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
- Stable under normal conditions 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid Stable under normal conditions.
- 10.5. Incompatible materials None in particular.
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects
Toxicological information of the product: VELATURE
a) acute toxicity Not classified
No data available for the product
b) skin corrosion/irritation Not classified
No data available for the product
c) serious eye damage/irritation Not classified
No data available for the product
d) respiratory or skin sensitisation
Not classified
No data available for the product
e) germ cell mutagenicity
Not classified
No data available for the product
f) carcinogenicity
Not classified
No data available for the product
g) reproductive toxicity
Not classified
No data available for the product
h) STOT-single exposure
Not classified
No data available for the product
i) STOT-repeated exposure
Not classified

383/8 Page n. 5 of 9



No data available for the product j) aspiration hazard Not classified No data available for the product Toxicological information of the main substances found in the product: 2-butoxyethanol - CAS: 111-76-2 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat 615 mg/kg Test: LD50 - Route: Skin - Species: Rabbit 405 mg/kg Test: LC50 - Route: Inhalation - Species: Rat 2.2 mg/l - Duration: 4h

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

VELATURE The product is classified: Aquatic Chronic 3 - H412 2-butoxyethanol - CAS: 111-76-2 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish 1474 mg/l - Duration h: 96 Endpoint: EC50 - Species: Algae 1550 mg/l - Duration h: 48 Endpoint: EC50 - Species: Daphnia 1840 mg/l - Duration h: 72 terbutryn - CAS: 886-50-0 reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Daphnia 0.1 mg/l - Duration h: 48 - Notes: daphnia magna Endpoint: EC50 - Species: Algae 0.048 mg/l - Duration h: 72 - Notes: pseudokirchneriella subcapitata Endpoint: EC50 - Species: Fish 0.22 mg/l - Duration h: 96 - Notes: oncorhynchus mykiss Endpoint: NOEC - Species: Algae 0.00064 mg/l - Duration h: 48 - Notes: skeletonema costatum Endpoint: NOEC - Species: Daphnia 0.004 mg/l - Duration h: 504 - Notes: daphnia magna Endpoint: NOEC - Species: Fish 0.098 mg/l - Duration h: 672 - Notes: oncorhynchus mykiss Endpoint: NOEC - Species: Algae 0.0012 mg/l - Duration h: 72 - Notes: pseudokirchneriella subcapitata 12.2. Persistence and degradability N.A.

- 12.3. Bioaccumulative potential
 - N.A.
- 12.4. Mobility in soil

N.A.

- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
 - None

SECTION 13: Disposal considerations

```
13.1. Waste treatment methods
```

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

383/8

Page n. 6 of 9



- 14.2. UN proper shipping name N.A.
- 14.3. Transport hazard class(es)
- N.A.
- 14.4. Packing group N.A.
- 14.5. Environmental hazards

```
N.A.
```

- 14.6. Special precautions for user limited quantity: N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) 2015/830 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: **Restriction 3 Restriction 40** Restrictions related to the substances contained: No restriction. Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 None

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

- H319 Causes serious eve irritation.
- H315 Causes skin irritation.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H332 Harmful if inhaled.
- H301 Toxic if swallowed.
- H410 Very toxic to aquatic life with long lasting effects.
- H318 Causes serious eye damage.

383/8 Page n. 7 of 9



H400 Very toxic to aquatic life.H317 May cause an allergic skin reaction.H314 Causes severe skin burns and eye damage.H311 Toxic in contact with skin.H330 Fatal if inhaled.

Hazard class and hazard category	Code	Description
Acute Tox. 1	3.1/1/Inhal	Acute toxicity (inhalation), Category 1
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Skin Sens. 1B	3.4.2/1B	Skin Sensitisation, Category 1B
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the

383/8 Page n. 8 of 9



specific use intended. This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS: GefStoffVO:	European Inventory of Existing Commercial Chemical Substances. Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Áviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.