The best there is

ma i c

HZ750, HZD750

The 750 models, like the 570 and 900's, are available in a choice of two specifications. The HZ750 is a single motored model and the HZD750 is a twin motored unit.

The main difference between the 750 and 900 models is the all steel construction from top to bottom; power head, filter module, container and heavy duty chassis. By design the complete assembly can be removed from its chassis, by a single toggle action, as may be required, in some instances, for decontamination purposes.

Heavy duty all steel

chassis release system.

Accessory kit

IMPORTANT INFORMATION Correctly selected and maintained the HZ series will form a valuable part of any system designed to control hazardous and health endangering dusts in the environment. It is important, however, to ensure the correct consideration is given to the appropriate clothing and protection required by the operator in A choice carrying out any specialist operation.

of MicroFlo or HepaFlo fine-dust baas

HZ kits see specification table



www.numatic.co.uk

www.numatic.fr



HZ Specifications

Numatic

Model	Motor	Power	Suction	Airflow	Kit	Capacity	Filtration	Range	Weight	Size
HZ200	1200W	50/60Hz	2500mm	42L/sec	BB17	9L	H*	26.8 m	10.1kg	355x355x520mm
HZ250						8L			11.5kg	340x340x455mm
HZ370					BB18	10L			10.4kg	355x355x570mm
HZ570					BB19	23L			17.1kg	415x415x645mm
HZD570	2400W			84L/sec					19.3kg	
HZ750	1200W			42L/sec	BB20	35L			19.8kg	510x510x960mm
HZD750	2400W			84L/sec					22kg	
HZ900	1200W			42L/sec		40L			25kg	800x490x880mm
HZD900	2400W			84L/sec					27.2kg	
* H Class to IEC 60 335-2-69										

www.numatic.de www.numatic.ch www.numatic.nl www.numatic.co.za

Numatic International Limited, Chard, Somerset, TA20 2GB Tel: 01460 68600 Fax: 01460 68458 Numatic International Limited 2012. Specification subject to change without prior notice. PN 244150 12/12



ETTO




HZ range...

The HZ series of machines are designed to collect H class dusts. All models operate to a 99.997% filter efficiency, H14 HEPA and tested to IEC 60 335-2-69.

HZ200, HZ370, HZ250



The three small machines within the HZ range only vary in the container size and construction. The universal HZ power head is of all steel construction and incorporates a full TwinFlo motor, service centre handle, bag full indicator and NuCable plugged cable system



as standard. The HEPA H14 filter unit is mounted in an all steel secure module with a separate primary pre-filter in the container itself and all machines are designed to operate together with our high efficiency HepaFlo dust bags to ensure excellent performance and easy, clean and safe emptying.

High hazard dusts under complete control

mate

HZ570, HZD570

The midrange HZ570 series provides a choice of Simplex HZ570 one motor or Duplex HZD570 two motored models.

1911P

The Duplex models have a 100% increase in AirFlo over the Simplex units and would be the preferred selection where larger volumes of fine material need to be collected.

The Power head is of all steel construction fitted with one or two TwinFlo motors, service centre handle with bag full indicator, NuCable plugged mains cable system and power outlet socket as standard.

The H class filter module is securely mounted within our all steel housing and provides an efficiency standard of 99.997% in use. The container is of a one piece Structofoam construction.

Our high efficiency system ensures superb operational performance using either HepaFlo or MicroFlo dust bags.



Transit safety cap top and bottom

NuCable allows easy cable replacement

HZ900, HZD900

Larger capacity and mobility whilst incorporating all the advanced features of the 570 models

Available in one motored HZ900 or two motored HZD900 models, and designed to provide increased capacity and mobility whilst incorporating all the many advanced features of the 570 models.

An important consideration when selecting a machine for the collection of hazardous dusts is that, quite often, the dust itself is by definition "fine dust" and, in this respect, the in roFlo bag option provides operational performan

- to a cceptionally high standard
- con ed with the ideal
- syst for clean and safe
- em ıg.

Standard power outlet socket Simplex 2000W power outlet Duplex 1000W power outlet

H class Micro filter