



CONSERVATION  
TECHNOLOGY  
& MACHINERY LTD

Importers and Manufacturers of Specialist Tractors and Machinery



Tractors for Life

**Maxter 60**

*The 48hp Quad tractor  
with a 1.5 ton lift capacity*



Available as SN with articulated steering, or RS with standard front steering, the Maxter's compact's size and build allows it to maintain a low centre of gravity, whilst guaranteeing a high level of stability when using heavy machinery in particularly difficult working conditions.



The Maxter is equipped with rear standard two-speed independent PTO, synchronised with the gearbox. The hydraulic lift with Category 1 three-point linkage has a lift capacity of a whopping 1500 kg and also comes with a standard double acting auxiliary outlet with rear push/pull connectors.

The engine used in the Maxter is a 3-cylinder VM water-cooled engine that gives a proven reliability. Designed to offer brilliant results, thanks to the optimised power/torque ratio, this engine is able to supply maximum torque at an extremely low engine rate.

The transmissions used in the Maxter tractors have been designed for equal -wheeled tractors to guarantee the right ratio for all jobs, while maintaining the simplicity that makes them indestructible throughout the years.



*Front axle oscillation*

## **A small, low centre of gravity tractor with a big tractor attitude**

The Maxter SN with it's tight turning circle for row crop work and confined areas.

The Maxter RS for excellent performance on slopes with heavy implements.

**Goldoni's Maxter series is right at the very top of its category when it comes to compact size and important weights. The narrow wheelbase but solid weight of the tractor make the Maxter a compact machine but with the right weight for guaranteeing both stability and strength.**



Maxter was designed to be a low centre of gravity tractor with a compact and agile shape. Its strong bearing structure gives an optimum weight distribution (50% at the front and 50% at the rear when an implement is attached).



Maxter is the ideal machine for working between the narrowest of crop rows whilst providing the utmost in comfort for the operator, with its height and weight adjustable seat and comfortable working position.

Maxter's four equal-sized wheels provide excellent wheel grip in every situation, on heavy soil, sloping or rugged ground, thanks in part to the front axle which can swing up to 15 degrees, allowing it to follow the contours of the ground, even in the worst conditions, providing a surprising amount of power for such a compact tractor.



The braking system, which acts on the rear wheels of the tractor, features large oil-cooled multiple plates that guarantee optimum braking efficiency in all conditions, but only requiring very low maintenance.



The hydraulic circuit, with its 38 litres per minute flow rate and 2 double-acting supplementary control valves with quick push-pull couplings, is able to satisfy the requirements of implements used for specialist farming purposes.



Maxter tractors have a 540/750 rpm independent PTO that's synchronised with the gearbox and features a 1 3/8 " profile which allows most of the implements available on today's market to be used.

# The Ultimate "Quad" Tractor

Specifications overleaf.



**Maxter 60 SN**

**Designed for  
the people  
who drive them.**

**Maxter 60 RS**



**Their compact and agile  
shape offer greater  
precision and efficiency  
whilst working.**

**Tight turning radius.**



**Powerful and reliable  
engines.**

**Toughly built transmissions.**

**Efficient in all conditions.**



**A high flow rate for all  
implements.**

**Power whenever needed.**



*A 48hp Goldoni Maxter  
side-by-side with a  
25hp compact  
tractor.*

**STRONG  
AGILE  
COMPACT**



# SPECIFICATIONS



Tractors for Life

"We at Goldoni believe that time is our friend.

When we make a machine, we do so because we are convinced that it must last a long time and always guarantee the safety and reliability for which you chose it."

	Maxter 60 SN	Maxter 60 RS
Engine Type	VM, 3-cylinder water-cooled diesel direct injection	
Power	48 hp, 2082 cc	
RPM	2600	
Fuel & Tank Capacity	Diesel, 30 litres	
Transmission	12+4 synchronised	16+16 synchronised with reverse shuttle
PTO	Independent at 540 / 750 rpm, synchronised with gearbox speeds	
Steering	Hydraulic with central articulation	Hydraulic
Rear Lift	Hydraulic, lever controlled, Class 1 3-point hitch Lift capacity 1500 kg	
Pump Flow Rate	38 ltrs/min	
Brakes	Rear oil-cooled multiple-plate type	
Clutch	Dry monodisc, diameter 230 mm	
Differential	Front: Mechanical system with manual locking through lever Rear: Mechanical system with manual locking through pedal	
Weight	1650 kgs	
Dimensions	Overall length, 3.25m Width, Min & Max: 1106-1404 mm SN, 1253-1632 mm RS	
Wheels	280/70x18" standard or low ground pressure tyres	

The best way to lengthen the life of your tractor and reduce down time to the very minimum is to rely on the Goldoni Routine Maintenance Service.

Only Goldoni has stocks that ensure the part you need will still be available for up to 40 years after your tractor model is no longer produced. Goldoni provides an ON-LINE ordering system for all workshops and can also make urgent deliveries for speedier repairs."



To discuss your requirements in further detail,  
please do not hesitate to contact us at:

**C.T.M.**

**Conservation Technology & Machinery Ltd**

**Units 1 & 2 Brocca Bank, Low Row, Richmond, North Yorkshire, DL11 6PR**

**Tel: 01748 886622**

**[www.goldonitractors.com](http://www.goldonitractors.com)**

**Email: [enquiries@ctmltd.co.uk](mailto:enquiries@ctmltd.co.uk)**

