

Electrical wire rope winches

Electrical wire rope winch BETA SL

Short times to delivery are followed by long periods in operation: the electric wire rope winch BETA SL in its standard design works permanently reliably due to enclosed worm gear pairs or spur gears

with high-quality brake motors. The electric wire rope winches BETA SL are available with a contactor control system including a gear limit switch.

Equipment

- Maintenance-free worm gear pairs or low-maintenance spur gear with milled and ground gears – running in oil bath
- Very quiet running by diagonal interlock
- Electrically released spring-applied disk brake
- Duty ratio S3 – 40 %
- Range of temperature: -20 °C – +40 °C
- Powerful three-phase motor for multi-range voltage 380 – 420 V / 50 Hz or 440 – 460 V / 60 Hz
- Motor protection type IP 55
- Grooved rope drum
- Large wire rope capacity
- Contactor control 42 V
- Gear limit switch
- Electronic overload protection as of 1000 kg lifting load
- According to the accident prevention provisions BGV D8

Options selectable

Options


Size	Capacity	Control	Mechanical
SL0	250 kg	Control pendant	./.
SL1	500/630 kg	Control pendant or frequency converter	Pressure roller or slack rope switch, alternatively combination of pressure roller and slack-rope switch
SL2	980/1250 kg	Control pendant or frequency converter	Pressure roller or slack rope switch, alternatively combination of pressure roller and slack-rope switch
SL3	2000 kg	Control pendant or frequency converter	Pressure roller or slack rope switch, alternatively combination of pressure roller and slack-rope switch

Delivery time for versions control pendant, pressure roller or slack rope switch approx. 10 days

Delivery time for version frequency converter approx. 25 days



Option: pressure roller



Option: slack rope switch



Option: control pendant



Option: frequency converter



BETA SLO



BETA SL1 – SL3

Electrical wire rope winches

Electrical wire rope winch BETA SL

Technical data

Art. no.	Size	Capacity 1 st layer	Rope speed	FEM	BGV	Voltage	Power	Rope Ø*	Rope capacity 1 st layer	top layer	A	B	C Ø	F	G	H	L	M Ø	
Contactor control with gear limit switch		kg m/min.					kW	mm	m	m	mm	mm	mm	mm	mm	mm	mm	mm	
	Type code																		
40063758	SL0	250	2.5	1 Bm	D8	400V	0.25	4	7	46.7	185	170	12	389	432	241	180	64	
31140006	SL0	250	4.7	1 Bm	D8	400V	0.37	4	7	46.7	185	170	12	389	432	241	180	64	
40062946	SL1	500	6.8	1 Am	D8	400V	0.75	6	6.7	48.9	215	300	13.5	740	340	340	200	86	
40062989	SL1	630	6.8	1 Bm	D8	400V	0.75	6	6.7	48.9	215	300	13.5	750	340	345	200	86	
40062990	SL2	980	6.0	1 Am	D8	400V	1.1	9	11	77.5	270	400	18	920	465	475	250	175	
40062993	SL2	1250	6.0	1 Am	D8	400V	1.1	9	11	77.5	270	400	18	930	465	480	250	175	
40062996	SL3	2000	6.8	1 Bm	D8	400V	2.2	12	10	74.5	320	510	22	1070	570	614	300	175	

*recommended rope: DIN 3069 FE-znk-1960 sZ-spa

