

fall protection only

### **ILE'O**

REF. NUS140



# FALL ARREST AND RESCUE HARNESS WITH WORK POSITIONING BELT AND PIVOTING RINGS





**REGULATION** 

**CERTIFICATION** 

neofeu.com

2016 / 425

EN 361:2002 EN 358:2018 EN 1497:2007 EN 813:1997



### **COMFORT / ACCESSORIES**



REMOVABLE BACK PAD WITH BREATHABLE 3D FABRIC



LARGE LEGS AND POSITIONING BELT WITH BREATHABLE 3D FABRIC



AUTOMATIC ALUMINUM BUCKLES WITH LOCKING INDICATOR



TOOL HOLDERS(X2) + LARGE TEXTILE STRINGS FOR TOOL HOLDING (X3)



**REMOVABLE LANYARD HOLDER (X2)** 

### **ATTACHMENT POINTS**



FRONT FALL ARREST ATTACHMENT POINT WITH WEBBING LOOPS TO LINK



BACK FALL ARREST ATTACHMENT POINT WITH ALUMINUM D RING



VENTRAL SUSPENSION ATTACHMENT POINTS BY WEBBING LOOPS TO LINK



LATERAL ATTACHMENT POINTS WITH ALUMINUM PIVOTING D RING FOR WORK POSITIONING

### **SAFETY**



**DROP INDICATORS** 



## TECHNICAL SPECIFICATIONS

- Water repellent webbing in polyester 44 mm (R ≥ 25 kN)
- Adjustment of shoulder straps, belt and leg straps height through quick buckles
- Chest strap 44 mm with automatic aluminum front buckle
- Back D ring in anodised forged aluminium
- Lateral attachment points with forged aluminum pivoting D ring for work positioning
- Front suspension and sternal attachment points on webbing loops to connect together
- Large legs with breathable 3D fabric and automatic alu buckle
- Large positioning belt with breathable 3D fabric, adjustable on height with 3 large textile strings for tool holding
- Removable back pad with breathable 3D fabric to facilitate the donning of the harness and increase the comfort of the user
- Drop indicator showing at 300 daN
- Static resistance ≥ 15kN
- · Weight: 2,5 kg

Removable accessories included:2xLanyard holders (Ref: NPORTL).

#### **USE**

For heavy use in sectors like ski lifts, industrial maintenance, windmills, energy, and masts.


### **DESCRIPTION**

**ILEO** is a versatile and ergonomic harness with a large work positioning belt and a breathable back pad with many adjustment possibilities to ensure the highest comfort and the quickest donning.

Its belt design with large lateral positioning D rings enables the user to rotate while working and offer a very good back support.

It is made of very resistant water repellent webbings for workers with tools up to 140 kg and is fitted with many tool-holders.

### **SIZES**



80 cm ≤ Size S ≤ 105 cm 90 cm ≤ Size M-L ≤ 115 cm 100 cm ≤ Size XL ≤ 135 cm

65 cm ≤ Size S ≤ 105 cm 85 cm ≤ Size M-L ≤ 120 cm 105 cm ≤ Size XL ≤ 130 cm

45 cm ≤ Size S ≤ 65 cm 50 cm ≤ Size M-L ≤ 75 cm 60 cm ≤ Size XL ≤ 80 cm

155 cm ≤ Size S ≤ 175 cm 165 cm ≤ Size M-L ≤ 188 cm 170 cm ≤ Size XL ≤ 200 cm

### REFERENCES

NUS140S	Size S
NUS140ML	Size M/L
NUS140XL	Size XL