



CERTIFICATION : EN 361 : 2002 / EN 1497 : 2007 / REGULATION : 2016 / 425

Dorsal plate in polypropilene with
fall arrest attachment ringFront attachment points
(loops to connect together)High resistance webbing
and stitchesPadded leg straps with
automatic bucklesSteel D ring on
back attachmentQuick fastening
chest strapSteel automatic locking
buckles on legsSteel quick adjustment
buckle on shoulders

TECHNICAL SPECIFICATIONS

- Main webbing in polyester wide 45 mm ($R \geq 22$ kN)
- Secondary chest strap elastic, wide 25 mm
- Black epoxy coated buckles on shoulders and legs
- Padded leg straps for better comfort
- Static resistance ≥ 15 kN
- Weight : 1,2 kg

Other model available on request :

- Back extension strap Ref. : NUS65AEX

USE

Full body harness for all types of works on height. Intended for industry and construction area. Rescue harness for all kind of rescue works.

DESCRIPTION

Full body harness and rescue harness NUS65A, offers safety and comfort of use through its automatic buckles on legs and quick buckles on shoulders for easy adjustment.

TAILLE / SIZE	
	80 cm \leq Size S \leq 105 cm 90 cm \leq Size M-L \leq 115 cm 100 cm \leq Size XL \leq 135 cm
	65 cm \leq Size S \leq 105 cm 85 cm \leq Size M-L \leq 120 cm 105 cm \leq Size XL \leq 135 cm
	45 cm \leq Size S \leq 65 cm 50 cm \leq Size M-L \leq 75 cm 60 cm \leq Size XL \leq 80 cm
	155 cm \leq Size S \leq 175 cm 165 cm \leq Size M-L \leq 188 cm 170 cm \leq Size XL \leq 200 cm