

## Technical data model EGV PSL

Model	EGV PSL 1016 II <i>new</i>	EGV PSL 1225	EGV PSL 1229	EGV PSL 1235
Art.-No.	192021784	040040503	040040504	040044421
Actuation	electric	electric	electric	electric
Operation	pedestrian	pedestrian	pedestrian	pedestrian
Capacity (up to 2.5 m lift), kg	1000	1200	1200	1200
Load center c, mm	600	600	600	600
Wheelbase y, mm	1165	1190	1190	1190
Weight (with battery), kg	363	481	496	531
Tyre type <sup>1</sup>	PUR/VG+PUR	PUR+VG/PUR	PUR+VG/PUR	PUR+VG/PUR
Steering rollers, mm	186x50+125x45	250x76+150x40	250x76+150x40	250x76+150x40
Load rollers, mm	82x70	82x70	82x70	82x70
Number of wheels/load rollers (x=driven)	1x+1/2	2+1x/2	2+1x/2	2+1x/2
Height, mast retracted h1, mm	1970	1780	1980	2250
Free lift h2, mm	1510	-	-	80
Stroke, mm	1510	2410	2810	3410
Height, mast extended h4, mm	1970	2985	3385	3915
Fork height max. h3, mm	1600	2500	2900	3500
Height of control handle max. h14, mm	1365	1390	1390	1390
Fork height lowered h13, mm	90	90	90	90
Overall length L1, mm	1675	1825	1825	1825
Length incl. apron L2, mm	522	675	675	675
Overall width b1/b2, mm	794	850	850	850
Fork height s, mm	60	70	70	70
Fork width e, mm	150	150	150	150
Fork length l, mm	1153	1150	1150	1150
Clearance fork tip-roller, x	365	365	365	365
Outside dimension of forks b5, mm	560	560	560	560
Ground clearance m2, mm	20	20	20	20
Aisle width pallet Ast, mm	2120	2075	2075	2075
Turning circle radius Wa, mm	1344	1460	1460	1460
Travel speed with/without load, km/h	3.7/4.3	4.0/5.0	4.0/5.0	4.0/5.0
Lifting speed with/without load, m/s	0.11/0.18	0.08/0.12	0.08/0.12	0.08/0.12
Lowering speed with/without load, m/s	0.18/0.18	0.4/0.1	0.4/0.1	0.4/0.1
Gradient with/without load, %	9/25	5/10	5/10	5/10
Service brake	electric	electric	electric	electric
Drive motor rating, kW	0.35	0.7	0.7	0.7
Hoist motor rating, kW	2.2	2.2	2.2	2.2
Battery	starter	starter	starter	starter
Battery charger, V/A	24/12	24/12	24/12	24/12
Battery voltage, V/Ah	24/70	24/92	24/92	24/92
Type of control	impulse	impulse	impulse	impulse

<sup>1</sup>PUR... Polyurethane, VG... Solid rubber

