



### Electric pallet truck model EGU PS 22AC

**Capacity 2200 kg**

Electrical drive, electrical lifting

Ideal unit for working within a warehouse environment for long haul and medium to high work load applications. Also ideal for working on ramps or on a lorry.

**Features**

- Compact and agile.
- Low maintenance A.C. drive technology.
- 210Ah traction battery for long working cycles.
- Creep speed button for pin-point work in confined spaces.
- Reliable impulse control for stepless regulation of driving speed.
- Digital display for battery status

**Scope of delivery**

- Battery and external charger include

**Technical data model EGU PS 22AC and model EGU PS 22AC FP**

Model	EGU PS 22AC	EGU PS 22AC FP
Art.-No.	040052450	040052451
Actuation	electric	electric
Operation	pedestrian	driver platform
Capacity, kg	2200	2200
Load center c, mm	600	600
Wheelbase Y, mm	1368	1368
Weight (with battery), kg	512	525
Tyre type <sup>1</sup>	PUR/PUR	PUR/PUR
Steering rollers l x d, mm	230x75	230x75
Load rollers l x d, mm	84x70	84x70
Number of wheels/load rollers (x=driven)	1x +2/4	1x +2/4
Stroke h3, mm	120	120
Fork height max. h15, mm	205	205
Height of control handle max. h14, mm	1323	1323
Fork height lowered h13, mm	85	85
Overall length L1, mm	1815	1965
Fork height s, mm	60	60
Fork width e, mm	160	160
Fork length l, mm	1150	1150
Outside dimension of forks b1, mm	540	540
Aisle width pallet Ast, mm	2305	2305
Turning circle radius Wa, mm	1640	1640
Travel speed with/without load, m/s	5.8/6.0	5.8/6.0
Lifting speed with/without load, m/s	0.19/0.35	0.19/0.35
Lowering speed with/without load, m/s	0.30/0.27	0.30/0.27
Gradient with/without load, %	9/15	9/15
Service brake	electric	electric
Drive motor rating, kW	1.0 (AC)	1.0 (AC)
Hoist motor rating, kW	0.8	0.8
Battery	traction	traction
Battery voltage, capacity at 20 h, V/Ah	24/210	24/210
Type of control	Curtis	Curtis

<sup>1</sup> PUR ... Polyurethane