

CBB 62193CBB

COOL BLUE BOOST – OFF-ROAD | Halogen headlight lamps for cars



Product datasheet

Technical data

Electrical data

Power input	75 / 68 W ¹⁾
Nominal voltage	12.0 V
Nominal wattage	100/90 W
Test voltage	13.2 V

¹⁾ Maximum

Photometrical data

Luminous flux	850/550 lm
Luminous flux tolerance	±15 / ±15 %

Dimensions & weight

Length	82.0 mm
Diameter	17.0 mm
Product weight	23.70 g

Lifespan

Lifespan B3	100 / 200 h
Lifespan Tc	200 / 400 h

Additional product data

Base (standard designation)	P43t
-----------------------------	------

Certificates & standards

ECE category	-
--------------	---

Country specific categorizations

Order reference	62193CBB
-----------------	----------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899437296	CBB 62193CBB	Hard Cover Box 2	- x - x -		
4052899437302	CBB 62193CBB	Shipping carton box 20	260 mm x 242 mm x 122 mm	7.68 dm ³	1544.00 g
4052899437654	CBB 62193CBB	Hard Cover Box 2	114 mm x 49 mm x 106 mm	0.59 dm ³	139.40 g
4052899437661	CBB 62193CBB	Shipping carton box 20	260 mm x 242 mm x 122 mm	7.68 dm ³	1544.00 g
4052899439023	CBB 62193CBB	Hard Cover Box 2	114 mm x 49 mm x 106 mm	0.59 dm ³	110.40 g
4052899439030	CBB 62193CBB	Shipping carton box 20	260 mm x 242 mm x 122 mm	7.68 dm ³	1544.00 g
4052899439788	CBB 62193CBB	Hard Cover Box 2	114 mm x 49 mm x 106 mm	0.59 dm ³	110.40 g
4052899439795	CBB 62193CBB	Shipping carton box 20	257 mm x 242 mm x 121 mm	7.53 dm ³	1544.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.