

2825

ORIGINAL | Lamps with glass wedge bases



Areas of application

- Position and parking light
- Indicator, brake, fog and reversing lights
- Number plate and side position lights
- Interior lighting and reading lights
- Instrument and switch lighting

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Product datasheet

Technical data

Electrical data

Power input	5 W
Nominal voltage	12.0 V
Nominal wattage	5.00 W
Power input tolerance	±10 %
Test voltage	13.5 V

Photometrical data

Luminous flux	50 lm
---------------	-------

Dimensions & weight



Length	26.8 mm
Diameter	10.0 mm
Product weight	1.30 g

Lifespan

Lifespan B3	350 h
Lifespan Tc	1000 h

Additional product data

Base (standard designation)	W2.1x9.5d
-----------------------------	-----------

Certificates & standards

ECE category	W5W
--------------	-----

Country specific categorizations

Order reference	2825 5W12VW2.1X
-----------------	-----------------

Product datasheet

Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300838632	OSRA2825	8328258	4739284	-
4050300925684	OSRA2825BLI2	-	4730323	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300838632	2825	Unpacked 1	30 mm x 11 mm x 14 mm	0.00 dm ³	2.30 g
4050300524801	2825	Folding carton box 10	46 mm x 29 mm x 112 mm	0.15 dm ³	24.00 g
4008321094469	2825	Shipping carton box 50	148 mm x 115 mm x 55 mm	0.94 dm ³	150.00 g
4050300925684	2825	Blister 2	95 mm x 70 mm x 18 mm	0.12 dm ³	12.58 g
4008321140340	2825	Shipping carton box 20	123 mm x 105 mm x 92 mm	1.19 dm ³	116.80 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.