

Instructions for all AQUABAG Filters:

Turn off your pool filter before installing and confirm that all return hose connections are tight (if applicable).

When Using A Pool Filter Return Fitting Connection:

- 1) Install an adapter fitting in your return inlet (hand tight if threaded).
- 2) Attach your AQUABAG over the end of the fitting, and secure it by tying or by utilizing the Reusable Nylon Tie included with your AQUABAG.

When Using A Pool Filter Return Hose Connection:

- 1) Disconnect the return hose where it connects to the pool, plug the hole or close the valve (if present).
- 2) Slip your AQUABAG over the end of the return hose approximately five inches and secure it with the Reusable Nylon Tie included with your AQUABAG. For larger hoses, simply trim off the narrower section of neck.
- 3) Place the AQUABAG into the pool. Its position does not matter, but it should be far enough inside the pool that it does not "hang" from the hose.

CAUTION: If the hose and bag slip out of the pool, you may accidentally drain your pool.

If possible, tie the hose to the pool or tie a weight of some kind to the hose and place it in the pool to prevent the hose from exiting the pool.

USE: Turn on your filter and your AQUABAG will begin collecting particles. As it collects the debris, it may begin to darken. This is normal. If the pool has extremely high levels of debris, be sure to occasionally check the firmness of the bag. As it becomes blocked with debris, pressure can build inside the bag, causing it to feel firm to the touch. **If this pressure gets too high, the bag may burst.**

When in the process of clearing particulates and removing your AQUABAG, it is normal for some material to be released into the pool. Simply clean and reinstall. Continue filtering until no escaping material is observed.

To Clean: The nylon tie can be removed by pressing the release tab. Hold the bag with the neck down and rinse it with a strong spray from a garden hose. Slipping it over a small pole (like a net handle) can make this easier. Usually just spraying from the outside will be enough. If you have a "straight" hose nozzle, it can be slid up into the bag to remove additional accumulation.

If you have any problems with your AQUABAG, please see our FAQ at www.theaquabag.com. If you need additional assistance, please send an email to support@theaquabag.com