

AFTER-SALE SERVICE

Purchase Date	(Year)	(Month)	(Date)
Warranty Period			
Purchase Store			

Please paste the store's stamp and guarantee barcode here, Please notice the purchase date should be confirmed when you buy the product.

内页5

WARRANTY SERVICE

Please follow the below solutions to confirm the defective problems before asking for warranty service.

Phenomenon	Solution
Separate bulb	Light off Defective lamp body: please connect a new lamp body with the original driver, if it works well, then it means the previous lamp body is defective, please cut down the power line of the defective lamp body for warranty.
	Light off Defective driver: please connect another new driver with the original lamp body, if it works well, then it means the previous driver is defective, please cut down the power line of the defective driver for warranty.
	Abnormal light Please connect suitable canbus decoder to solve the canbus problem.
ALL in one bulb	Flicking Please connect suitable canbus decoder to solve the canbus problem.
	Flicking If encounter the situation when lighting up the bulb for some times it do not work suddenly, and then turn off the power start it again work well, please change the dust cover with more space for heat dissipation to solve it.
	Flicking Please connect suitable canbus decoder to solve the canbus problem.
	Light off Please make sure of correct installation, if the lamp body is still not work, please cut down the power line of the defective lamp body for warranty.
Abnormal light Please connect suitable canbus decoder to solve the canbus problem.	
Flicking If encounter the situation when lighting up the bulb for some times it do not work suddenly, and then turn off the power start it again work well, please change the dust cover with more space for heat dissipation to solve it.	

Attention:
The following conditions are beyond warranty scope.
1. Canbus problem: when replace the original halogen bulb with LED bulb, some vehicles may meet with canbus problem like light flickering etc, please connect suitable decoder to solve the canbus problems.
2. Man-made reason: man-made reason lead to broken led chip, chapped wire, user modify or repair the bulb themselves etc.
3. Installation problem: some vehicles may can not install our product because of small installation space or installation position doesn't fit etc.
4. Natural disaster: damage because of irresistible natural disaster like earthquake, flood etc.

内页6

WARRANTY SERVICE

Thank you for being the best part of NOVSIIGHT.

Please contact us if there is any problem with headlights, we will response you in 24 hours.

底页

PRODUCT MANUAL

封面

H7

1 Pull up the socket

2 Install and fix the socket

3 Insert the lamp body as the direction of arrow

4 Please screw the bulb on clockwise

5 Connect the power line with original car lamp connector

Tips
If the wires is not enough to contact please use additional adapter.

内页1

H4/H1/H3

1 Please move off the chuck

2 Insert the lamp body as the direction of arrow

3 Connect the power line with original car lamp connector

内页2

H8/H9/H10/H11/H13/9004/9005/9006/9007/880/881

1 Insert the lamp body as the direction of arrow

2 Please screw the bulb on clockwise

3 Connect the power line with original car lamp connector

内页3

PRODUCT SPECIFICATION

Operating Voltage	DC9-32V
IP Rate	IP68
Color Temperature	6500K
Heat Dissipation Theory	Aviation aluminum ADC12
Operating Life	>100000hrs
Operating Temperature	-40°C~+80°C

内页4

尺寸:100x72mm

材质:80克双胶纸 黑白 折页