



EXCEL

BUTYL RUBBER CAULK # 1232



Product Description

Butyl Rubber Caulk is an elastomer-based sealant for use on many dissimilar building surfaces. It has exceptional adhesion to common construction surfaces such as metal, glass, wood, brick, stone and paint. It is ideal for sealing narrow openings in mobile homes, skylights and application of vapour barrier. Is also recommended for joints in Preserved Wood Foundations (PWF).

Features and Benefits

- Exhibits strong adhesion and flexibility over extreme temperature ranges.
- Good paint ability after 24 hour drying period. (depending on temperature)
- Water-resistant.
- Up to 10 YEARS LIFE EXPECTANCY
- LEED Compliance..... Eligible for credit EQ 4.1 VOC <160g/L

Application

Apply only to clean, dry and sound surfaces. If old caulk is brittle or crumbling, remove it. Use in joints no more than .95cm(3/8") should be built up to within .95cm (3/8") with suitable back-up material.

RESTRICTIONS: Do not apply when temperature is below 4.4°C(40°F). Care should be taken when using product on plastic as crazing may result. If in question do a small test area first.

Trim nozzle to desired bead size, puncture membrane at inner base of nozzle, and apply with standard caulking gun. Clean tools with mineral spirits.

Coverage

25 Linear feet per 300ml @ .64 cm X .64 cm (1/4"X1/4")
300ml & 825 ml Cartridges

Cautions

- Combustible! Keep away from heat and open flame.
- Do not take internally.

Cautions

- KEEP OUT OF THE REACH OF CHILDREN

Physical Properties

% SOLIDS	90% by weight
SLUMP RESISTANCE	VERY GOOD
THROUGH DRY TIME	7-14 DAYS
PAINTABILITY	GOOD
FLASH POINT	40°C (100°F)
SERVICE TEMPERATURE RANGE	-34 °C to +82°C (-30°F TO +180°F)

Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.