



EXCEL

Technical Data Sheet



BLACK JACK WET PATCH ROOF CEMENT # 2172

Product Description

This product is a convenient to use cartridge grade all weather roof cement for stopping leaks. pointing, sealing, bonding, etc. May also be used for tacking loose shingle tabs.

Features and Benefits

- Versatile – Use on dry or damp surface.
- Waterproof – Forms a tight, strong seal: stays soft and pliable.
- Easy to use – Apply using a standard caulking gun.

Application

When application is to take place at temperatures below 50°F (10°C), store the Roof Cement at room temperature for 24 hours prior to use in order to make gunning easier. If required Wet Patch Roof Cement may be tooled with a trowel or putty knife.

Emergency repairs to wet surfaces should be considered temporary and should be redone, if needed, when weather conditions improve. Clean up with mineral spirits

Coverage

1/4" by 1/4" bead will cover 24 linear feet per 300ml cartridge.

Cautions

- Combustible: Contains petroleum distillates.
- Keep away from heat, sparks, and open flame.
- Use only with adequate ventilation.
- Wet Patch Roof Cement should not be painted.

Physical Properties

Flash Point	>45°C
Non-Volatile	70% Min. by weight
Through Dry time	2 to 3 days
Service temperature,	-28°C to + 65.5°C (-20°F to +150°F)
Effect of weathering	Slight Chalking
Water Resistance: (Good drainage)	Excellent

Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.