



EXCEL

ACOUSTICAL SEALANT # 2210



Product Description

Excel Acoustical Sealant is a blend of synthetic rubber polymers formulated primarily to bond polyethylene vapour barrier sheeting. It has excellent adhesion to common construction surfaces. May also be used as a bedding compound over vibrating elements, electrical boxes or other items recessed or passing through walls. Excel Acoustical Sealant should only be used in concealed areas.

Features and Benefits

- Will not dry out, stays flexible with long lasting adhesion over a broad range of temperatures.
- Excellent adhesion to most substrates.
- Compatible with EPS and ISO Insulation.
- Reduces the sound transmission of partition systems.
- Not damaged by freezing.
- LEED Compliance..... Eligible for credit EQ 4.1 VOC <140g/L

Application

Application surfaces should be clean, dry, and free from grease, oil and loose particles. Apply bead onto surface and cover within 24 hours to prevent dirt pickup that may inhibit adhesion to the sheeting.
Application Temperature Range: 2° C- 40°C (35°F-100°F)
Clean up with Mineral Spirits.

Coverage

8 m (26 Linear feet) per 300 ml tube @ 6 mm (1/4") X 6mm (1/4")
22m (72 Linear feet) per 825 ml tube @ 6mm(1/4") X 6mm (1/4")

Cautions

- Not to be used on freshly treated wood. (Should be aged at least 6 months)
- Cannot be painted.
- Use in well ventilated areas.
- Combustible, Contains petroleum distillates
- Keep away from open flames.

- Keep out of reach of children.

Physical Properties

Colour:.....Dark Gray
Recycled content:.....8% nominal
Solids:.....85% Min by weight
Specific Gravity:.....1.6Kg/L +/- 0.2Kg/L

Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.