



EXCEL

Technical Data Sheet



**EXCEL CRACK CRETE:
A PATCHING GROUT FOR
CONCRETE AND MORTAR # 2910**

Product Description

A fast drying latex-based product provides a quick and easy repair to cracked concrete sidewalks, driveways, steps, sills, gutters and culverts. May also be used on cracked foundation, for tuck pointing, patching stucco, as well as brick and stone surfaces.

Features and Benefits

- * Resists Cracking
- * Excellent Adhesion
- * Interior or exterior use
- * Concrete Color

Application

Apply only to sound, clean and dry surfaces. Use in joints no more than .9CM (3/8") wide by .9CM (3/8") deep with a suitable back-up material.

Restrictions: Apply only when surface temperature is above 4°C (40°F). Do not apply when rain is imminent, rain can damage product within 12 hours after application.

Trim nozzle to desired bead size, puncture membrane at inner base of nozzle and apply with standard caulking gun. Clean up hands and tools with soap and water.

Coverage

25 lineal ft per 300 ML CARTRIDGE. 64mm X 64mm (1/4"X1/4") bead

Cautions

KEEP FROM FREEZING

Physical Properties

Generic Type.....	ACRYLIC Latex Based
Specific Gravity.....	1.2 Kg/L
Dry Time (Cured).....	1-2 Days
Resistance to Oil & Solvents.....	Excellent
Resistance to Water (Cured).....	Excellent

Clean Up (immediately)..... Water & Soap

Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.