



4502 Patching Fabric Universal

- Reinforces repair
- Prevents cracks from reappearing
- Longer-lasting repair

DESCRIPTION: Universal Patching Fabric is a durable membrane designed to reinforce asphalt roof patching, white roof patching, stucco and masonry patches and driveway products while repairing cracks, holes, seams and joints. Its durable open mesh weave assures thorough bonding and allows for expansion and contraction.

PREPARATION: Remove any old and dried out cement, caulking, or coating from cracks or holes. Surface should be dry and clean. If surface is metal, it should be rust and scale free.

USES: Recommended for use with asphalt roof patching, white roof patching, stucco and masonry patches and driveway products. Use on: Roofs, Gutters, Chimneys, Copings, Drain Pipes, Foundation Walls, Flashings around TV aerials, Skylights, Ventilators and all roof projections.

APPLICATION: Apply Universal Patching Fabric with patching compound. Fill up cracks or holes with patch to the surface. Trowel small amount of patch at one end of crack, open joint or loose seam as starting point for fabric. Center fabric over crack, seam or hole, and spot stick fabric in patch. Unroll the fabric to cover defective area, leaving a 2" minimum overlap on all sides. Sandwich the fabric by covering with a additional layer of patch, extending at least 2" beyond the fabric on all sides. Smooth and trowel to a feathered edge. Before applying patch and fabric to a blistered area, cut the blister in a criss- cross manner. Open up blisters and fold flaps back, removing any rotted materials and drying out any moisture from underneath the blister. Trowel patch to cover exposed area and bond old surfaces together. Fold cut flaps back to original position and press into place. Cover with fabric and patch, using the same method as with cracks and holes.

PRECAUTIONS: Avoid eye and skin contact. Loose fibers can cause irritation. Cloth or leather gloves are recommended. Store in a dry place.

LIMITED WARRANTY: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
4502-GA	6" x 50"	6" x 3" x 3"	1 roll	8.2 oz.	12/crtn	025056450203

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101