



GH INTERNATIONAL SEALANTS ULC
 2540 RENA ROAD
 MISSISSAUGA, ONTARIO, L4T 3C9
 CANADA
 1-905-677-5522

PRODUCT: NON-FIBRATED ALUMINUM COATING

CODE: 5320

SECTION 01: IDENTIFICATION

Supplier identifier..... GH INTERNATIONAL SEALANTS ULC
 2540 Rena Road
 Mississauga, ON. L4T 3C9
 1-905-677-5522

Product identifier..... NON-FIBRATED ALUMINUM COATING

Product code..... 5320

Product use..... Aluminium roof coating.

Emergency telephone number..... CANUTEC 24-hour number (613-996-6666). CHEMTREC 1-800-424-9300.

SECTION 02: HAZARD IDENTIFICATION



Hazard classification..... Flammable Liquids — Category 3. Skin Irritation — Category 2. Carcinogenicity — Category 2. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity - Single Exposure - Category 3 (narcotic effects). Specific Target Organ Toxicity — Repeated Exposure — Category 1 .

Signal word..... DANGER.

Hazard statement..... H226 Flammable liquid and vapour. H315 Causes skin irritation. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H336 May cause drowsiness or dizziness. H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure. H373 May cause damage to hearing organs through prolonged or repeated exposure.

Precautionary statements..... P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharge. P260 Do not breathe mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P307+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. P308+P313 IF exposed or concerned: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash before reuse. P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container to an approved waste disposal plant.

Other hazards..... None.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	WT. %
Asphalt	8052-42-4	10-12
Stoddard Solvent	8052-41-3	10-15
Light aromatic solvent naphtha, petroleum	64742-95-6	18-22
White spirit	not available	5-6
Xylene (mixed isomers)	1330-20-7	4-6
Ethylbenzene	100-41-4	1-1.5

PRODUCT: NON-FIBRATED ALUMINUM COATING**CODE: 5320****SECTION 04: FIRST-AID MEASURES**

Routes of exposure	
Inhalation.....	Remove to fresh air. If irritation persists, consult a physician. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical aid as soon as possible.
Ingestion.....	Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.
Skin contact.....	Wash off with soap and water. Get medical attention if irritation develops and persists. Take off contaminated clothing and wash before reuse.
Eye contact.....	Promptly flush with large amounts of cold water for at least 15 minutes. If irritation persists, consult a physician.
Most important symptoms and effects, both acute and delayed	The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.
Medical attention and special treatment.....	IF exposed or concerned: Get medical advice/attention. Treat symptomatically. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Extinguishing media.....	Use water spray or fog, foam, carbon dioxide or dry chemical. Do not use water jet as an extinguisher, as this will spread the fire.
Hazardous combustion products.....	Harmful vapours. Carbon monoxide, carbon dioxide, hydrocarbons, metal oxides.
Special protective equipment and precautions	Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.
Sensitivity to static discharge.....	Expected to be sensitive. Take precautionary measures against static discharge.
Sensitivity to mechanical impact.....	Product is not sensitive to mechanical impact.
Further information.....	Vapors are heavier than air and may flow along surfaces to remote ignition sources and flash back . Cool closed containers exposed to fire with water spray. During fire, gases hazardous to health may be formed.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protective clothing. Eliminate all sources of ignition. Ventilate area if indoors. Restrict access to area until completion of clean up. Evacuate personnel to safe areas. Ensure clean up is conducted by trained personnel only . Local authorities should be advised if significant spillages cannot be contained.
Environmental precautions.....	Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply. Ventilate the area. Prevent further leakage or spillage if safe to do so .
Methods and materials for containment and cleaning up	Cover with plastic sheet to prevent spreading. Contain and absorb spilled liquid with non combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal. Flush with water. Do not flush into surface water or sanitary sewer system. Nonsparking tools should be used. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Contaminated absorbent material may pose the same hazards as the spilled product . Do not place into containers where ignition sources such as cigarettes or other ignition sources may be discarded. For waste disposal, see section 13 of the SDS .

SECTION 07: HANDLING AND STORAGE

Handling precautions.....	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Keep container closed when not in use. Wear appropriate personal protective equipment. Do not get in eyes, on skin or on clothing. Avoid inhalation of mists/vapours/fumes. Wash thoroughly after handling. Keep container tightly closed .
Storage needs.....	Keep in a dry, cool and well-ventilated place. Keep containers from excessive heat and freezing.
Materials to avoid.....	Keep away from strong acids. Keep away from strong bases. Keep away from oxidizing agents.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Asphalt	0.5 mg/m ³	not available	not available	not available		not available
Stoddard Solvent	100 ppm	not available	500 ppm	not available		not available
Light aromatic solvent naphtha, petroleum	not available	not available	not available	not available		not available
White spirit	not available	not available	not available	not available		not available

PRODUCT: NON-FIBRATED ALUMINUM COATING

CODE: 5320

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm	150 ppm	100 ppm
Ethylbenzene	20 ppm	no data available	100 ppm	no data available	100 ppm
Engineering controls.....	Good general ventilation (typically 10 air changes per hour) should be used .				
Individual protection measures					
Eye/type.....	Safety glasses with side-shields.				
Clothing/type.....	Wear clean long legged, long sleeved work clothes.				
Gloves/ type.....	Wear chemical protective gloves made of nitrile or neoprene.				
Respiratory/type.....	Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.				
Hygiene measures.....	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke during work. Remove soiled clothing and wash it thoroughly before reuse.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance.....	liquid.
Color.....	goldish to silverish liquid.
Odour.....	solvent odour.
Odour threshold.....	no data available.
pH.....	not applicable.
Melting point (°C).....	no data available.
Freezing point (°C).....	no data available.
Initial boiling point (°C).....	154.
Flash point (°C), Method.....	45 CC.
Evaporation rate.....	no data available.
Upper flammability limit (% vol).....	7.
Lower flammability limit (% vol).....	0.8.
Vapour pressure (mm Hg).....	2.
Vapour density (air=1).....	no data available.
Relative density/Specific Gravity.....	1.0.
Water solubility.....	insoluble.
Solubility in other solvents.....	no data available.
Partition coefficient — n-octanol/water.....	no data available.
Auto ignition temperature (°C).....	254.
Thermal decomposition temperature.....	no data available.
Viscosity.....	no data available.
% volatile by volume:.....	45-65.

SECTION 10: STABILITY AND REACTIVITY

Reactivity.....	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability.....	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions.....	No hazardous reactions when stored and handled according to instructions. The product is chemically stable.
Conditions to avoid.....	Keep away from heat. Keep away from sources of ignition. Keep away from incompatibles such as oxidizing agents .
Incompatible materials.....	Acids and bases. Strong oxidizing agents.
Hazardous decomposition products.....	Decomposition will not occur if handled and stored properly. In case of fire, oxides of carbon (CO and CO ₂), fumes and smoke may be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Asphalt	not available	>5,000 mg/kg (oral-rat); >2,000 mg/kg (dermal-rabbit)
Stoddard Solvent	>5.0 mg/l (Inhalation-rat, 4H mist)	>5,000 mg/kg (oral-rat); >2,000 mg/kg (dermal-rabbit)
Light aromatic solvent naphtha, petroleum	>76.3 mg/l (inhalation-rat, 4h)	>5,000 mg/kg (oral-rat); >2,000 mg/kg (dermal-rabbit)
White spirit	>13.1 mg/l (Inhalation-rat, 4 hours)	>15,000 mg/kg (oral-rat); >3,400 mg/kg (dermal-rabbit)

PRODUCT: NON-FIBRATED ALUMINUM COATING

CODE: 5320

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Xylene (mixed isomers)	11.3 mg/l (Inhalation. rat, 4H)	4,300 mg/kg (oral, rat); 1,700 mg/kg (dermal, rabbit)
Ethylbenzene	17.2 mg/l (Inhalation. rat, 4H)	3,500 mg/kg (oral, rat); 15,340 mg/kg (dermal, rabbit)
Routes of exposure		
Inhalation.....	Inhalation of vapours may cause irritation to the nose, throat and respiratory tract.	
Ingestion.....	Ingestion of this product may cause nausea, vomiting and diarrhea.	
Skin contact.....	May cause irritation.	
Eye contact.....	Contact may cause eyes irritation.	
Acute effects		
Acute oral toxicity.....	Acute toxicity estimate > 2,000 mg/kg. Virtually nontoxic after a single ingestion. Method: calculation method.	
Acute dermal toxicity.....	LD50 (Rabbit) : > 2,000 mg/kg. Virtually nontoxic after a single skin contact. Method: calculation method.	
Acute inhalation toxicity.....	Acute toxicity estimate : > 20 mg/l. Exposure time: 4 h. Virtually nontoxic by inhalation. Method: calculation method.	
Skin corrosion/irritation.....	Result: Moderate skin irritation.	
Serious eye damage/eye irritation.....	Result: Mild eye irritation.	
Respiratory or skin sensitisation.....	Non-sensitizing.	
Specific target organ toxicity (STOT) single exposure	Inhalation may cause narcosis.	
Aspiration hazard.....	No aspiration hazard expected.	
Chronic toxicity/effects		
Specific target organ toxicity (STOT) repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure. Excessive inhalation of Xylene has caused hearing loss in laboratory animals.	
Carcinogenicity.....	Asphalt is listed as IARC Group 2B (possibly carcinogenic to humans). Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).	
Reproductive toxicity.....	Animal studies have shown Xylene to cause fetotoxic effects at dosage levels at or near maternal toxicity levels.	
Germ cell mutagenicity.....	No known significant effects or critical hazards.	
Remarks.....	The product has not been tested. The statement has been derived from the properties of the individual components.	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	May cause long-term adverse effects in the aquatic environment.
Persistence and degradability.....	The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.
Bioaccumulative potential.....	No data available.
Mobility in soil.....	No data available.
Other adverse effects.....	No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods	
Waste disposal of substance.....	The disposal of the product must be made in an approved sanitary landfill or in a foundry in accordance with state, provincial and/or federal regulations.
Container disposal	Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

SECTION 14: TRANSPORT INFORMATION

TDG classification.....	UN1999, Tars, Liquid, Class 3, PGIII .
-------------------------	--

SECTION 15: REGULATORY INFORMATION

WHMIS regulatory status.....	This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015). This product is WHMIS 2015 controlled.
------------------------------	---

PRODUCT: NON-FIBRATED ALUMINUM COATING

CODE: 5320

SECTION 16: OTHER INFORMATION

Disclaimer..... The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

Prepared by: CanChem Consultant

Preparation date..... APR 09/2017