



EXCEL

Technical Data Sheet

EXCEL ASPHALT ROOF & CONCRETE PRIMER # 6001



Product Description

Excel #6001 is an Asphalt based primer for use prior to the application of hot asphalt, fibrated asphalt coatings, asphalt emulsions, reflective coatings or asphalt adhesives. It is suitable for concrete, wood or weathered built-up roofing. It is not recommended for use on Coal tar coated roofs.

Meets... ASTM D-41

Features and Benefits

- Promotes adhesion
- Seals surface prior to application of fibrated materials.
- Re-saturates and prolongs the life of dried out roofing felts.

Application

Sweep off all dust, dirt and debris. Roof should be completely dry before applying primer. Apply with roofing brush, paint brush, mop or spray equipment. In cold weather, keep this product in a heated room until time of application. Normally, a properly applied coat of primer will be glossy, even if dry to touch. If surface appears dull after being coated with primer, the primer has been absorbed and a second coat should be applied. Always stir or shake thoroughly before using. Clean up with Mineral spirits

Coverage

Coverage depends on the absorbing qualities of the surface being coated. If first coat becomes completely absorbed, apply a second coat. Normal rate of application is 4-6L per 9.3m² (100 sq. ft.).

Cautions

- Combustible: Keep away from heat, sparks and open flame. Use only with adequate ventilation.
- Avoid prolonged or repeated contact with skin.
- Not intended for interior applications.

- Not for use as a primer for peel and stick membranes.

Physical Properties

Flash Point > 45°C
Specific Gravity 0.89- 0.91Kg/L
Total Solids by weight..... 50% min.
Drying Times..... 2-4 Hours

Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.