



# 6007F

## MS-201 BONDING AGENT Data Sheet



### Bonding Agent for Tape

- E-Z & Fast spray application
- Primes surface for self-adhering membranes
- Provides maximum tack
- Quick setting
- Ideal for cold weather use

**DESCRIPTION:** Black Jack® MS-201 Bonding Agent is an aerosol primer used with MS-400 Building Tape that promotes superior adhesion. Perfect to use around window and doors and flashings in cooler weather. Allows for great adhesion and sealing when cold temperatures reduce the adhesion of the membranes.

**USES:** For vertical or horizontal surfaces. Apply to wood, metal, gypsum board, masonry, concrete to promote adhesion. May also be used as a roofing primer. Designed to dry fast with a 3 minute tack time.

**APPLICATION:** Shake well before using. Apply to clean, dry surface. After using product, clear out spray tip in the following manner: Turn can upside down and point into refuse can. Push spray head for 3 seconds to clear passage of product. If valve clogs, remove from can and clean in paint thinner.

**LIMITATIONS:** Do not use on foam surfaces, including isocyanate foam (ICF) construction.

**COVERAGE RATE:** One 425g spray can covers 3m<sup>2</sup> (33 ft<sup>2</sup>).

**CLEAN-UP:** Paint thinner.

**PRECAUTIONS:** For exterior use only. Protective clothing and eyewear should be used during application of this product. Solvent in this product will damage polystyrene insulation. For applications above -12°C. Do not use in drinking water or food systems. Do not use on EPDM, Hypalon, PVC, single ply or synthetic surfaces. If there is any question regarding compatibility, test a small section first. Protect from freezing.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	6.8-7.3 lbs.
Residue by Evaporation, %	52 min.
Consistency	Spray
Tack Time (50% Relative Humidity, 70°F)	30 minutes
Set Time Through (50% Relative Humidity, 70°F)	2 hours
Application Temperatures	-12°C-40°C
Clean-up Tools	Paint Thinner, Mineral Spirits
Color	Clear

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

425g spray can	1 lb.
----------------	-------



**DANGER**  
**FLAMMABLE**  
**POISON · IRRITANT**  
**CONTENTS UNDER PRESSURE**

CONTENTS MAY CATCH FIRE. CONTENTS HARMFUL. CONTAINER MAY EXPLODE IF HEATED. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not smoke. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not puncture. Do not burn. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Store away from heat. Wear a respirator. Keep out of reach of children.

**FIRST AID TREATMENT:** Contains: Toluene, Acetone, 1,1,2-trichloroethylene, Isobutane, Propane. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.

Product is asbestos free.

**WARRANTY AND DISCLAIMER:** For limited warranty and disclaimer information, contact the Gardner-Gibson, Inc. corporate office at 1-800-237-1155.

©2013 GH International

**Distributed by**  
GH International  
2540 Rena Road  
Mississauga, Ontario  
L4T 3C9

See MSDS for more info

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com