

6030F



AQUA-TITE Data Sheet

Foundation Waterproofing Sealant

- Seamless, flexible finish
- Liquid applied sealant
- E-Z application
- For below grade applications

DESCRIPTION: Black Jack® Aqua-Tite is a liquid, gel based coating designed for below grade waterproofing on vertical walls. It is ideal to use on masonry, cinderblock and concrete block walls, stucco, brick, retaining walls, basements and foundations walls. The rubberized finish prevents water, moisture and air, from penetrating surfaces. Can also be used to help seal and protect underground wood and metal surfaces. Dries to a green color that can be painted.

PREPARATION: Clean or power wash surfaces to be coated. Salt deposits (efflorescence), peeling or blistered paint, dirt, dust, chalk, grease, and form release agents must be removed prior to application. Remove all rust or loose paint from metal surfaces. Patch cracks and seams with Black Jack® MS-100 Flexible Sealant, and feather for a smooth surface. Do not apply over damp or wet surfaces. Apply only after concrete and masonry has cured and is dry.

APPLICATION: Formulated to be used when air and surface temperatures are above 10°C and rising. Stir thoroughly prior to and during use. Apply with a heavy nap paint roller directly to walls to be waterproofed. A professional airless sprayer can also be used. A minimum two full coats are required for proper protection.

DRY TIME: Allow 1-2 hour dry time between coats.

COVERAGE RATE: This pail will cover a surface area of 10,7m² in a 2 coat application. Aqua-Tite needs to be applied to a wet film thickness of 1.75mm (70 mils) and should not exceed 2.6mm (100 mils) during each coat. Final dry thickness after 2 coats needs to be a minimum of 0.8mm (30 mils).

CLEAN UP: Tools should be cleaned with soap and water.

PRECAUTIONS: For exterior use only. Do not freeze. Protective clothing and eyewear should be used during application of this product. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 38°C. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	10.19
Residue by Evaporation, %	37.50
Combustible Solvents	0%
Consistency	120-130 KU
Cure Time (at recommended coverage)	3 hours-Dry to Touch/ 72 hours- Full Cure
Application Temperatures	Above 32° F
Flammability (Flash point, °F solvent)	245° F
Clean-up Tools	Water

Approx. Shipping Weights: (Note: All approx. weights include container.)

18.9 L	50.95 lbs.
--------	------------

KEEP OUT OF REACH OF CHILDREN.

VOC: less than 50 g/L

LIMITED WARRANTY: Gardner-Gibson, Inc. warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for the product, is free of defects in material and workmanship for a period of 12 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/ OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

© 2013 GH International

Distributed by:
GH International
2540 Rena Road
Mississauga, Ontario
L4T 3C9

See MSDS for more info

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com