



6452

DRIVE-KOTE 500 FILLER AND SEALER Data Sheet

- Renews Blacktop Surfaces
- Enhanced With Latex

**Black Jack® Drive-Kote™ 500** is a good quality blacktop filler and sealer designed for asphalt pavements. This product helps renew the look of the driveway, and contains sand particles to help fill in small cracks in the surface. **Drive-Kote 500** contains latex to help durability.

**SURFACE PREPARATION:** Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer's season prior to application of any sealer. Driveways must be cleaned with **Driveway Kleen™**, spray on cleaner & degreaser before sealcoating. For oil stains, apply **Driveway Kleen™** liberally and scrub into surface to penetrate oil spots. This step promotes proper bonding and will help prevent adhesion failures. Repair cracks and holes with **Crack Stop Elastic Crack Filler** for longest lasting results. For cracks and holes larger than 1" use **Drive Patch**. For larger potholes use **RePave Permanent Pot Hole Patch** (allow 6 weeks to cure). All repaired areas must be allowed to cure, see product instructions for curing times.

**APPLICATION:** Temperatures must be at least 65°F and rising, but below 90°F for application. Rinse and clean driveway with driveway cleaner. Properly treat oil spots with cleaners, or sealer will not adhere and flake off. After driveway is rinsed thoroughly, apply sealer to the damp pavement. Mix well. Pour out 1/2 the container and work product across blacktop with brush or squeegee. Complete the entire driveway in one continuous application to prevent "color shading". Do not over apply, which will result in tracking. Do not apply if rain or cold temperatures are expected within 36 hours. This sealer is not recommended or warranted for use on surfaces which contain a slope greater than 20 degrees. Match batch codes, if possible.

**COVERAGE RATE:** Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Use a cross pattern of application to insure all voids are filled and sealed. Driveway must cure approx. 2-4 hours for foot traffic and 24-48 hours for vehicle traffic. Humid or cloudy conditions may prolong curing time. Two thin coats are strongly recommended. Thick coats will result in uneven coverage, tracking and drying problems. Apply second coat perpendicular to the first, after the first coat has cured (approx. 3-6 hours). When possible, match batch codes on lids when using multiple containers. Approximate Coverage for driveways in average condition: 350 sq. ft./5 gal. pail.

**CLEAN-UP:** While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

**PRECAUTIONS:** Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **CLOSE CONTAINER WHEN NOT IN USE.** Do not reuse empty containers. Dispose of in an environmentally acceptable manner, if not for yours, than for your children's sake. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. Caution should be taken on linoleum floors, which may experience slight discoloration from household traffic stains, including asphalt driveway sealers. Consult your linoleum manufacturer for suggestions. **KEEP FROM FREEZING.**

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	9.0-9.4 lbs,
Residue by Evaporation, %	35 ± 1.0
Combustible Solvents	None
Consistency	Brush, Roller or Squeegee
Cure Time (50% Relative Humidity, 70°F)	2 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	65°-100°F
Flammability	N/A waterbased
Clean-up Tools	Soap & water when wet Mineral spirits when dry

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

5 gallons (18.9L)	49 lbs.
55 gallons (208.2L)	540 lbs.

CAUTION! HARMFUL OR FATAL IF SWALLOWED

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not use in drinking water or food systems. In Case Of: Skin Contact: Wash thoroughly with soap and water. Flush thoroughly with clear water and contact a physician immediately.

**CAUTION! EYE AND SKIN IRRITANT  
KEEP OUT OF REACH OF CHILDREN**

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

**VOC:** less than 3.0 g/l

Asphalt	C.A.S.# 8052-42-4	Clay	C.A.S.# 1332-58-7
Fillers	C.A.S.# 14808-60-7	Latex	C.A.S.# 9003-55-8

Product is asbestos free

PATENT PENDING

© 2006 Gardner Asphalt

Manufactured by Gardner Asphalt, P.O. Box 5449, Tampa, FL 33675

WARRANTY AND DISCLAIMER:

**Drive-Kote 500** is guaranteed to maintain a protective film on your driveway surface for a period of five (5) years from date-of-purchase when applied according to our directions. If the product proves to be defective within 5 years of date of purchase, with your original retail receipt, it shall be replaced or refunded on a prorated basis. Gardner Asphalt will not be liable for areas that have ponding water, poor drainage problems, or snow removal damage. Failures due to acts of God, fire, structural defects or causes beyond our control are excluded from this guarantee and we are not responsible for labor or other costs incurred in the original or any replacement application. Except as stated above, we make no warranties or guarantees, expressed implied, and none should be inferred. For this guarantee to be valid, products produced by Gardner Asphalt must be used for repair. This warranty is only for residential (single family) homes. Two coats must be applied. Not applicable on commercial parking lots. If product wears away before the warranty period, a refund will be made based on the prorated cost vs. the life of the product.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com