



6453

DRIVE-MAXX 700 DRIVEWAY SEALER Data Sheet

- No-Stir Gel is Fast & E-Z to Apply
• Lasting Protection
• Renews Blacktop Surfaces
• Latex Enhanced for Longer Life

Black Jack® Drive-Maxx™ 700 is a better quality rubberized blacktop filler and sealer designed for asphalt pavements. This product renews the look of old worn driveways, and contains sand particles to fill in small cracks.

SURFACE PREPARATION: Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer's season prior to application of any sealer. Driveways must be cleaned with Driveway Kleen™, spray on cleaner & degreaser before sealcoating.

APPLICATION: Temperatures must be at least 65°F and rising, but below 90°F for application. Rinse and clean driveway with driveway cleaner. Properly treat oil spots with cleaners, or sealer will not adhere and flake off.

COVERAGE RATE: Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal.

CLEAN-UP: While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

PRECAUTIONS: Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Table with 2 columns: Property and Value. Rows include Weight Per Gallon, Residue by Evaporation, Combustible Solvents, Consistency, Cure Time, Full Cure, Application Temperatures, Flammability, and Clean-up Tools.

Approx. Shipping Weights: (Note: All approx. weights include container.)

Table with 2 columns: Volume and Weight. Rows include 5 gallons (18.9L) = 58 lbs. and 55 gallons (208.2L) = 630 lbs.

CAUTION! HARMFUL OR FATAL IF SWALLOWED

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye and skin irritant.

CAUTION! EYE AND SKIN IRRITANT KEEP OUT OF REACH OF CHILDREN

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm.

VOC: less than 6.0 g/l

Table with 4 columns: Material, C.A.S.#, Material, C.A.S.#. Rows include Asphalt Fillers and Clay/Latex.

Product is asbestos free

PATENT PENDING

© 2006 Gardner Asphalt
Manufactured by Gardner Asphalt, P.O. Box 5449, Tampa, FL 33675

WARRANTY AND DISCLAIMER:

Drive-Maxx 700 is guaranteed to maintain a protective film on your driveway surface for a period of seven (7) years from date-of-purchase when applied according to our directions. If the product proves to be defective within 7 years of date of purchase, with your original retail receipt, it shall be replaced or refunded on a prorated basis.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com