

# 6481F



## CLEAR CARE 600 WATERBASED SEALER FOR PAVERS & WALKWAYS Stellant à base d'eau pour pavés et allées Data Sheet

- Premium crystal-clear acrylic sealer for pavers, brick & masonry surfaces
- Siliconized for maximum performance
- Longest lasting protection
- Enhances natural beauty
- Seals against water and stains
- E-Z application and cleanup

### Can be used on:

- Exterior Concrete Surfaces (Vertical & Horizontal)
- Parking Garages
- Driveways
- Pool Decks
- Concrete Block, Stucco, Brick & Stone Walls
- Patios and Walkways
- Garage Floors and Sidewalks
- Epoxy Set Chatahoochee Stone
- Other Concrete & Metal Surfaces

### Product Advantages:

- Protects & beautifies concrete and natural stone surfaces
- Easy to apply
- Resists oil, gasoline & water
- Resists hot tire pick-up
- Durable and tough, long-lasting finish
- Will not peel, flake or fade
- Creates a like-new "wet look" shine

**DESCRIPTION:** Clear-Care™ 600 Waterbased Sealer for Pavers & Walkways is a premium blend of waterbased acrylic resins (30% solids) that forms a "new-look" finish to beautify, protect, and preserve masonry surfaces. The clear finish renews and enhances the natural color and beauty of the surface, and provides superior protection against moisture and wear, while resisting staining due to mold and mildew growth. The non-yellowing finish provides a tough yet flexible finish for the longest lasting protection. Low odor formula cleans up with soap and water when wet. Indoor or Outdoor use on: Brick, pavers, stone, concrete, Chatahoochee/river rock, garage floors, pool decks, driveways, sidewalks, roof tiles, patios, and decorative stone and masonry surfaces.

**PREPARATION:** All surfaces should be cleaned with cleaning products such as Driveway Kleen™, or pressure washed and scrubbed with bleach solution to remove organic growth. Area must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter before coating. Rusty metal must be cleaned with a wire brush and primed with a suitable primer before application of this product. Be certain all surfaces are thoroughly rinsed and dry prior to applying coating.

**APPLICATION & COVERAGE RATE:** Apply a thin even coat at 10.9 m<sup>2</sup> per liter per coat, depending on the surface. May be applied by brush, roller or airless sprayer. Dries to touch in 1 hour, may be longer in cooler temperatures. The floor may be subjected to light foot traffic in 12 hours for recoating purposes only. If two coats are desired or necessary, apply in the opposite direction of the prior coat within 48 hours. CAUTION: Coated surfaces may become slippery when wet. Adding a non-skid floor additive will help prevent slip. Adding a non-skid additive will reduce the life of the coating.

**CLEAN-UP:** Clean tools with soap and water.

**PRECAUTIONS:** Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 38°C. Do not reuse empty containers. Keep closed when not in use. Do not use in drinking water or food systems. PROTECT FROM FREEZING. For best results: do not thin, surface temperature must be minimum of 13°C and rising. Do not apply if heavy dew or rain is expected within 12 hours. Yearly inspection and maintenance will greatly enhance the life of the coating.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Sheen:	Semi-gloss
Weight Per Gallon, lbs.	8.47 lbs.
Solids % Vol:	20.9%
Solids % WT:	25.0%
Type of Cure:	Coalescence
Coverage Rate:	400 sq. ft./gal
Film Thickness:	4.0 mil wet/1.00 mils dry
Viscosity:	50 KU
Reduction Solvent:	Water
Dry Time:	1 hour

### Approx. Shipping Weights: (Note: All approx. weights include container.)

3.4L	8.5 lbs.
18L	42.5 lbs.

**NOTICE:** Yearly inspection is highly recommended. Repair any area as needed. This information is based on our best knowledge and experience. Since we have no control over application or conditions, our only obligation shall be to replace any material proved defective. We assume no liability for damage of any kind and the user accepts the product "as is". The suitability of the product for an intended use shall be solely at the discretion of the user.

**VOC:** less than 100 g/L

©2007 Gardner-Gibson, Inc.

www.gardner-gibson.com

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com