



# SHUR-STIK

Technical Data Sheet

## SHUR-STIK 111 HEAVY DUTY (CLAY) WALLCOVERING ADHESIVE FOR VINYL # 8711



### Product Description

A premium grade, clay based adhesive specifically formulated with high solids content to assure a fast grab and strong, durable bond. This adhesive is ideally suited for all heavy and difficult to install wall-coverings such as Type I-III Vinyl, heavyweight fabric, flexible wood, mylar and foil. Shur-Stik #111 has a class "A" Fire Rating.

### Features and Benefits

- \*EXCELLENT WET TACK
- \*ASTM FIRE RATED
- \*IDEAL FOR DRY HANGING
- \*MOLD & MILDEW RESISTANT
- \*EXTENDED WET EDGE
- \*FREEZE THAW STABLE
- \*WATER CLEAN-UP
- LEED COMPLIANCE..... Eligible for credit EQ 4.1 VOC <10g/L

### Application

#### PREPARATION:

SURFACES MUST BE CLEAN, DRY, SMOOTH AND STRUCTURALLY SOUND. Clean walls to remove dirt, grease, wax, paste residue and loose paint. Repair surface damage with SHUR-STIK LIGHTWEIGHT SPACKLING. Porous surfaces such as new drywall, plaster and latex painted walls should be sized or sealed with SHUR-STIK #SS76 SUPER SIZE (POWDER), #78 READY TO USE SIZING OR #23 ALL SURFACE PRIMER SEALER.

Non-porous surfaces such as plastic, glass, Formica, baked enamel, glossy paint or existing vinyl wall-covering should be primed with SHUR-STIK #23 ALL SURFACE PRIMER SEALER.

#### APPLICATION:

Add 285ml OF CLEAN WATER to 3.78L of adhesive. Apply evenly with paste brush or roller. Pasted strips should be folded and allowed to set for up to 10 minutes before hanging. Shorten time if temperature is over 27°C.

Apply adhesive directly to the wall surface for DRY HANGING.

The temperature and porosity of wall surface determine the amount of area pasted beyond one strip, as well as the speed of the applicator.  
Wash seams, trim and other areas as you proceed.

## Coverage

3.78L WILL HANG APPROX: 26m (280 sq.ft.) depending on surface and weight of material.  
Available in 6 X 946 ML, 4 X 3.78 L, 1 X 18.93 L & 20 Liters BIOBOX

## Cautions

Keep out of reach of children

## Physical Properties

Color..... Light Tan  
Freeze-Thaw Stable..... Yes (4-6 Cycles)  
Resistance To Mold/Mildew..... Excellent  
Open Time (Approx.)..... 20 Minutes  
VOC's..... <10gms/L

## Limited Warranty

If this product is proven to have a manufacturing defect, we will provide you with replacement value or product, at our option, for the defective product. This commitment is our full representation regarding the product and is in lieu of all expressed or implied warranties and may not be extended by representatives, written sales information, drawings or otherwise. IN NO EVENT SHALL THE MANUFACTURER OR ITS AFFILIATES BE LIABLE FOR ANY INDIRECT, ASSOCIATED, INCIDENTAL OR CONSEQUENTIAL DAMAGES.