



6001

Asphalt Roof and Concrete Primer

- Promotes adhesion
- Seals surface prior to application of fibrated materials.
- Re-saturates and prolongs the life of dried out roofing felts.

Black Jack® Asphalt Roof And Concrete Primer. This thin refined asphalt base coating recommended for saturating new or dried out roofing felts and concrete surfaces, before coating with fibrated asphalt coatings and mastics. Use also as a primer before applying asphalt adhesive to dry roofing paper or concrete.

PREPARATION: Sweep surface clean of all dirt and debris. Surface must be dry before the application of this primer. Repair all cracks, breaks or seams with Black Jack 6230 All Weather Roof Cement.

APPLICATION: Apply with a roller, brush or spray gun. In cold weather, keep material in heated area until ready to use to make application easier. Depending upon porosity and absorption qualities of surface, apply at the rate of approx. 4 to 8 litres per 9.3 m² (100 sq. ft.) If first coat becomes completely absorbed, apply a second coat. If primed surface is to be covered with aluminum roof coating, care must be taken that primer is not applied in excess.

COVERAGE RATE: Coverage depends on the absorbing qualities of the surface being coated. If first coat becomes completely absorbed, apply a second coat. Normal rate of application is 4-6L per 9.3m² (100 sq. ft.).

CLEAN-UP: Mineral spirits.

PRECAUTIONS: Combustible: Keep away from heat, sparks and open flame. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Not intended for interior applications. Not for use as a primer for peel and stick membranes.

COMPLIANCE: Meets ASTM D-41

WARRANTY AND DISCLAIMER: GHI warrants product to be free of material defects for a period of 12 months, the “Warranty Period,” from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, GHI shall, within its sole discretion and upon receipt of purchaser’s timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GHI TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES							
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	DRY TIME	FLASH POINT	SOLIDS BY WEIGHT	PACK	UPC
6001-9-30	18.93 L	30 cm x 30 cm x 37 cm	2-4 hours	45°C	50% min	1	065224600153