# Wagon Brakes & Light/Medium Duty

### **Wagon Brakes**

One of the most common problems on stage is how to quickly brake and then release rolling scenery. Wagon Brakes provide secure holding power, as well as fast, quiet releasing without the need for drilling holes in the stage floor. Mounted to the side of a platform or scenery, this brake actually lifts the scenery off its casters, preventing the wagon from shifting under active actor movements. A unique lever action pushes down a plunger, lifting even heavy pieces with only minimal force required from a stagehand. A minimum of two brakes per unit are recommended. Extension Spindle is required.

Cat. #	Description
GPHWBL	Wagon Brake Large-800 lbs
GPHSL	Spindle Large 3/8" x 3 1/2"
GPHWBS	Wagon Brake Small-300 lbs.
GPHSS	Spindle Small 5/16" x 2 1/2"

Each Wagon Brake is shown with corresponding extension spindle.





# Light Duty Casters #7-9 Series

- Load capacity 60 lbs.
- · Oilless wheel bearing
  - Bright zinc finish
- Dual ball bearing raceway in swivel
- No brake available on light duty series
- This furniture caster is very easy to conceal

		Type of	Wheel	Load
Cat. #	Type	Wheel	Diameter	Height
CS9-7DN	Rigid	Neoprene	1 3/4""	2 3/8"
CS25-7DN	Swivel	Neoprene	1 3/4"	2 3/8"




rigid

### Medium Duty Casters #4200 Series

- Load capacity 150 lbs.
- · Oilless wheel bearing
- Bright zinc finish
- Dual ball bearing raceway in swivel
- No brake available on #4200 series

#### **SWIVEL**







#### **RIGID**

	Type of	Wheel	Load
Cat. #	Wheel	Diameter	Height
CS4202-PRDN	Neoprene	2"	2 7/8"
CS4202-PRH	Hard Rubber	2"	2 7/8"
CS4202 1/2-PRDN	Neoprene	2 1/2"	3 5/8"
CS4202 1/2-PRH	Hard Rubber	2 1/2"	3 5/8"

rigid



# Medium Duty **=**

**Medium Duty Low Profile Casters #4730 Series** 

- Load capacity 300 lbs.
- Dual ball bearingwheels
- Greater floor protection
- Dual ballbearing raceway in swivel
- No brake available on #4730 series



### **SWIVEL**

	Type of	Wheel	Load
Cat. #	Wheel	Diameter	Height
CS4732-XDN	Neoprene	2"	3 1/4"
CS4732-XH	Hard Rubber	2"	3 1/4"
CS4732 1/2-XDN	Neoprene	2 1/2"	3 3/4"
CS4732 1/2-XH	Hard Rubber	2 1/2"	3 3/4"

Our most popular, and cost effective, stage platform caster. A must have for any school or community theatre!



swivel



### **RIGID**

	Type of	Wheel	Load
Cat. #	Wheel	Diameter	Height
CS4732-XRDN	Neoprene	2"	3 1/4"
CS4732-XRH	Hard Rubber	2"	3 1/4"
CS4732 1/2-XRDN	Neoprene	2 1/2"	3 3/4"
CS4732 1/2-XRH	Hard Rubber	2 1/2"	3 3/4"

rigid



- Load capacity 300 lbs.
- Soft round ball bearing
- Dual ball bearing raceway in swivel

Wheel Diameter	Load Height	Cat. #	Type of Wheel
3"	4 1/4"	CS4763-RXD CS4763-XD	Rigid Swivel
3 1/2"	4 3/4"	CS4763 1/2-RXD CS4763 1/2-XD	Rigid Swivel
4"	5 5/16"	CS4764-RXD CS4764-XD	Rigid Swivel
5"	6 5/16"	CS4765-RXD CS4765-XD	Rigid Swivel





rigid

# Medium Duty

# **#4760 Series Medium Duty Casters**

- Load capacity 350 lbs.
- Oilless wheel bearing
- Dual ball bearing raceway in swivel







### **Neoprene Wheels**

Wheel <u>Diameter</u> 2 1/2" 2 1/2"	Load Height 3 3/4" 3 3/4"	Cat. # CS4762 1/2-RDN CS4762 1/2-DN	Type of Wheel Rigid Swivel
3"	4 5/16"	CS4763-RDN	Rigid
3"	4 5/16"	CS4763-DN	Swivel
3"	4 5/16"	CS4763-DNB	Brake
3 1/2"	4 3/4"	CS4763 1/2-RDN	Rigid
3 1/2"	4 3/4"	CS4763 1/2-DN	Swivel
3 1/2"	4 3/4"	CS4763 1/2-DNB	Brake
4"	5 5/16"	CS4764-RDN	Rigid
4"	5 5/16"	CS4764-DN	Swivel
4"	5 5/16"	CS4764-DNB	Brake
5"	6 1/4"	CS4765-RDN	Rigid
5"	6 1/4"	CS4765-DN	Swivel
5"	6 1/4"	CS4765-DNB	Brake
6"	7 3/8"	CS4766-RDN	Rigid
6"	7 3/8"	CS4766-DN	Swivel

### **Hard Rubber Wheels**

Wheel <u>Diameter</u> 2 1/2" 2 1/2"	Load Height 3 3/4" 3 3/4"	Cat. # CS4762 1/2-RH CS4762 1/2-H	Type of Wheel Rigid Swivel
3" 3"	4 5/16" 4 5/16"		Rigid Swivel
3 1/2"	4 3/4"	CS4763 1/2-RH	Rigid
3 1/2"	4 3/4"	CS4763 1/2-H	Swivel
4"	5 5/16"	CS4764-RH	Rigid
4"	5 5/16"	CS4764-H	Swivel
5"	6 1/4"	CS4765-RH	Rigid
5"	6 1/4"	CS4765-H	Swivel
6"	7 3/8"	CS4766-RH	Rigid
6"	7 3/8"	CS4766-H	Swivel

## **#4160 Series Large Plate Theatrical Casters**

- Load capacity 350 lbs.
- Oilless wheel bearing
- Dual ball bearing raceway in swivel
- No brake available on #4160 series
- Only available in swivel

	Type of	Wheel	Load
Cat. #	Wheel	Diameter	Height
CS4163-DN	Neoprene	3"	4 5/16"
CS4164-DN	Neoprene	4"	5 5/16"
CS4164-H	Hard Rubber	4"	5 5/16"







### **#3170 Series**

- Precision ball bearings
- Wheel is solid elastomer
- Thread width is 1 3/8"

Wheel	Load		Type of	
Diameter	Height	Cat. #	Wheel	Capacity
3"	4 5/8"	CS31-73RPSE	Rigid	500 lbs
3"	4 5/8"	CS31-73PSE	Swivel	500 lbs.
4"	5 9/16"	CS31-74RPSE	Rigid	600 lbs
4"	5 9/16'	CS31-74PSE	Swivel	600 lbs.

# Heavy Duty **=**

# **#4170 Series Heavy Duty Casters**

- Load capacity 550 lbs.
- Dual ballbearing raceway in swivel
- Oilless wheel bearing







### Neoprene Wheels

Rigid

Swivel

Brake

Wheel	Load		Type of
Diameter	Height	Cat. #	Wheel
3"	4 7/16"	CS4173-RDN	Rigid
		CS4173-DN	Swivel
		CS4173-DNB	Brake
4"	5 7/16"	CS4174-RDN	Rigid
		CS4174-DN	Swivel
		CS4174-DNB	Brake
5"	6 7/16"	CS4175-RDN	Rigid
		CS4175-DN	Swivel
6"	7 9/16"	CS4176-RDN	Rigid
		CS4176-DN	Swivel

These may look old school, but this ancient caster really rolls! The best platform/scenery caster ever. Load it up!



# **#2SL Twin Wheel Casters Heavy Duty Low Level Casters**

- 2 7/16" overall height with twin 2" diameter wheels
- Can carry up to 600 lbs per caster on a smooth, hard floor
- Suitable for use with concert grand pianos, fireproof filing cabinets, safes and other heavy equipment
- · Swivel casters

Cat. #	Load Capacity	Wheel Type
CS2SL-NYWH	350 lbs	Twin Nylon
CS2SL-C1PL	600 lbs	Twin Semi-Steel
CS2SL-NYOL	350 lbs	Yellow Polyurethane

#### **Hard Rubber Wheels**

r			
Wheel	Load		Type of
Diameter	Height	Cat. #	Wheel
3"	4 7/16"	CS4173-RH	Rigid
		CS4173-H	Swivel
4"	5 7/16"	CS4174-RH	Rigid
		CS4174-H	Swivel
5"	6 7/16"	CS4175-RH	Rigid
		CS4175-H	Swivel
6"	7 9/16"	CS4176-RH	Rigid
		CS4176-H	Swivel





Got a flat? We have replacement inner tubes.

Wheel	Load		Type of
Diameter	Height	Cat. #	Wheel
8"	10"	CS418RPC	Rigid
8"	10"	CS418PC	Swivel
8"	10"	CS418T	Replacement Tube
8" 8" 8" 10"	12"	CS4110RPC	Rigid
10"	12"	CS4110PC	Swivel
10"	12"	CS4110T	Replacement Tube

The 10" wheels feature **Semi-Foam Care Free Tires**. You never have to put air in them! Truly worth the additional cost!

10"	12 1/4"	CS4110RPC	Rigid
10"	12 1/4"	CS4110PC	Swivel

# Heavy Duty & Triways

### **LH Heavy Duty Casters**

- Polished chrome finish
- Single ballbearing raceway in swivel
- No brake available on stem casters
- 1/2" x 1" NC threaded stem
- Only available in swivel
- Neoprene = Quiet

Cat. #

CSL32-XDN

CSL32-XAE

CSL83-XAE

CSL321/2-XKN

CSL321/2-XAE

- Elastomer = Harder/Easier to roll
- Corded Neoprene = Extra Strong
- Excellent when used with the Triway Plate



Load

Capacity

300 lbs.

400 lbs.

350 lbs.

400 lbs.

900 lbs.

#CSL32-XDN Twin Wheel

Type of

Neoprene

Elastomer

Elastomer

Elastomer

Corded Neoprene

Wheel



#CSL83-XAE Single Wheel





# Stem Casters for Pipe #CSLS63 #CSLS63WB

- Polished chrome finish
- Single ballbearing raceway in swivel
- Neoprene bushing for 1 1/4" or 1 1/2" I.D. Pipe
- Available with brake (WB) or without
- DN Wheel Type-Neoprene
- 3" Diameter

### Triway Swivel - "Turtle"

• Steel constructed body is the strongest made

Wheel

2"

2"

2 1/2"

2 1/2"

Diameter

- All ball-bearing construction
- Quiet, soft rubber wheel
- 900 lb load capacity



	VV IICCI	Loau	Loau	VV IICCI
Cat. #	Diameter	Capacity	Height	Description
CSTW2XDN	2"	900	5"	2" Double Neoprene
CSTW2XAE	2"	1200	5"	2" Double Elastomer
CSTW212XKN	2 1/2"	1100	5 7/16"	2 1/2" Double Corded Ne
CSTW212XAE	2 1/2"	1200	5 7/16"	2 1/2" Double Elastomer
CSTW3XAE	3"	2700	6 1/6"	3" Single Elastomer

We introduced "The Turtle" to the entertainment industry over 5 years ago so it only seems fitting that we offer the widest variety of Turtles today... You can also buy the plate alone so you can build whatever you want and rotate it!




Cat. # Description
CSTWP Plate Only - build whatever you like!

### 180 Series

- Load capacity 800 lbs.
- Four-sided double ball bearing
- Polyurethane wheels

Type of	Wheel	Load	
Wheel	Diameter	Height	Cat. #
Swivel	4"	5 15/16"	CS184T
Brake	4"	5 15/16"	CS184TB
Rigid	4"	5 15/16"	CS184RT
Swivel	5"	6 5/8"	CS185T
Swivel	6"	7 1/2"	CS186T
Swivel	8"	10"	CS188T







# Rubber Bumpers & Glides =

### **Rubber Impact Bumpers**

### **Doughnut Bumpers**

#CS63-A-813G

- Designed for installation on the ends of tubular handles
- Contains a steel insert
- · Attaches to wood or metal
- Color: grey



# **Corner Bumpers**

- Made with A-567 strip bumper
- Designed with 3/16" diameter bolt




## **Strip Bumpers**

#CS63-A-567G

- Designed for metal or wood surfaces
- Easy to apply and does not require a special channel
- Color: grey

### **Corner Bumpers**

#CS63-A-833G



- · Easily attached using self-taping sheet metal screws
- · Color: grey

#CS63-A-1676G

- holes for attachment

### **Single Prong Glides**

· Made of high carbon steel and nickel plated finish

<u>Cat. #</u>	Diamete
H46622	1/2"
H46623	5/8"
H46624	3/4"
H46625	7/8"



### **Deluxe Glides**

#H103

- Made of case hardened steel with a resilient rubber cushion and a nickel plated finish
- Size: Diameter 7/8"

### **Leveling Deluxe Glides**

#H104

- · Used for height adjustment
- Size: 1/4" x 1"





### **Three Prong Glides**

- Used on the bottom of objects, such as chairs, to help them glide
- 1 1/8" can be used for sliding scenery

Cat. #	Size	Diameter
H46601	1	3/8"
H46602	2	1/2"
H46603	3	5/8"
H46604	4	3/4"
H46605	5	7/8"
H46606	6	1 1/8"



#### Felt Gards®

- Felt guard pads with adhesive backing.
- Protects hardwood, linoleum, ceramic tile and other hard surfaces.

Cat. #	Diameter	#/pkg
CS9952	1"	16
CS9953	1 1/2"	8

### Magic Sliders®

- Slides everything as if it has wheels.
- For all appliances, foot furniture and scenery.
- Protects hardwood, linoleum, ceramic tile and other hard surfaces.
- •The concave is great for moving pianos.
- •The Grip Tech model stays on the leg better then anything we have seen.

Cat. #	Diameter	#/pkg	Move uo to
CS4025	1"	4	1600 lbs.
CS4125	1" w/Grip Tip	4	1600 lbs.
CS4225	1 1/4" w/Grip Tip	4	1600 lbs.
CS4050	2" Round	4	2500 lbs.
CS4124	15/16" x 4" rectangl	le 4	3200 lbs.
CS4600	2 3/8" concave	4	2500 lbs.
CS4100	4"	4	3200 lbs.



