



- 4) Center the fabric frame over the upper rear door locks using one of the fabric clips to keep in place. *Make sure that the fabric flap is facing the outside of the van.* Use another two clips to the right and left of center to keep the upper fabric frame in place as shown:



- 5) With the 5 upper fabric clips installed you can push the upper part of the gasket in place and you are ready to secure the sides of the frame into the gasket.



- 6) As you install the sides pushing the gasket back into the side of the van. Keep in mind to make sure the fabric is even all the way down on each side of the van. About $\frac{3}{4}$ " of an inch material is what should be behind the gasket to ensure the screen is not too tight so the magnetic flaps can close on their own.



- 7) Once you work your way all the way to the bottom we have left some excess material. A very small portion of material is to be trimmed. This will make it easier to install the gasket and frame around the lower corner.



- 8) With the outer frame in place the next step is to attach the bug net screen to the outer frame that is now installed. (***note: before zipping screen to outer frame make sure the RB logo is facing outwards, to the back of the van***). From the inside of the van you will want to zip the very top part of the screen to the top part of the bug screen frame as shown. Do the same for the sides.



- 9) The bug net screen can be accessed a few different ways. Either by the center pass through (*magnetic self-closing buttons*) or by un-zipping the sides.



- 10) The bug net screen also comes with clips at the top of the bug net. These clips are to be used when the screen is rolled up to keep out of the way. Great when loading or unloading the rear of the van.



11) The bug net comes with a magnetic flap. Once the doors are opened this flap is to be flipped back up into place and lowered or open when the doors need to be closed.



12) Installation is complete