



"XL" Deluxe Automatic Blood Pressure Monitor

Model: MW701 f

Cuff Detection (CD)



Detects and indicates whether the cuff is wrapped around the arm properly

Movement Detection



The "Movement Detection" helps reminding the user to remain still and is indicating any body movement during measurement. The specified icon appears once a "body movement" has been detected during and after each measurement.



- Cuff Detection
- Movement Detection
- Hypertension Risk Indication
- Irregular Heartbeat Detection (IHB)
- Average of Last 3 Readings
- 7 day AM/PM Averaging
- 120 Memories for 2-users With Date and Time Indication
- Guest Mode
- Latex-Free Patented Universal Cone Cuff
- Large LCD size : 101*118 mm
- Adaptor Socket
- Lifetime Calibration
- PC Link (Optional)
- Zipper Bag



Cuff Detection




Movement Detection



Hypertension Risk Indication



Irregular Heartbeat Detection (IHB)



Average of Last 3 Readings



120 Memories for 2-Users With Date and Time Indication



Guest Mode



Universal Cone Cuff



7 Day AM/PM Averaging



Jumbo Size "XL" Digit



Dual Power Ready



Mobile Calibration System



Clinically Validated

This blood pressure monitor has passed the criteria of the European Society of Hypertension by achieving all requirements and achieved the highest possible grade (A/A) according to the criteria of the British Hypertension Society. This monitor further complies with the standard required by the Association for the Advancement of Medical Instrumentation (AAMI).



Universal Cone cuff fits arm circumference: 24-40cm (9.4"-15.7")
Other size cuffs available upon request

Real **f**uzzy Technology

Real Fuzzy Technology determines ideal cuff pressure based on one's systolic blood pressure and arm size. Users no longer need to pre-set the inflation level before measurement. The technology eliminates arm discomfort through unnecessary high inflation settings and also prevents inaccurate readings caused by erroneous cuff inflation levels.

Model	Qty per carton	Carton volume
MW701f	12 pcs	0.060 cbm/ctn
QTY per 20'	QTY per 40'	QTY per 40'HQ
5592 pcs	11196 pcs	12996 pcs

- Storage and Transportation Condition
-10°C~60°C(14°F~140°F)
10%~90% RH, 700~1060 hPa