

DT301 Series

Rugged Tablets

Slim, Rugged, Multi-functional Wireless Computing



The DT301 Series Rugged Tablet features the integration of a high brightness 10.1" capacitive touch screen and a high performance, energy-efficient Intel® processor within a slim, lightweight, durable package. With built-in Wi-Fi and Bluetooth as well as options for barcode scanner, 3D camera, GNSS, and 4G connection, this robust tablet offers seamless information capture and transmission for improved workflow. Rated IP65, MIL-STD-810G and MIL-STD-461F, the DT301 Series Rugged Tablet provides reliable operation in harsh, mission-critical environments.

Features




- Intel® Celeron® or 8th Generation Core™ i5/i7 processor
- Microsoft® Windows® operating system
- 10.1" sunlight readable capacitive touch screen (800 nits), digital pen support
- High capacity, hot-swappable battery pack
- IP65-rated for water and dust resistance
- MIL-STD-810G for shock and vibration protection
- MIL-STD-461F for EMI and EMC tolerance
- Build-in smart card/ CAC reader (DT301C/ CT301T)
- Optional Intel® RealSense™ Depth camera (DT301X), 2D barcode scanner
- Optional long range Bluetooth, GNSS, 4G LTE



Applications

- Government/ Military
- Inventory/ Warehousing
- Control/ Monitoring
- Hospitality
- Retail
- Healthcare
- Manufacturing
- Construction
- Utilities/ Smart City
- Logistics
- Law Enforcement

Specifications

			
Model	DT301C	DT301T	DT301X
System			
CPU	Intel® Celeron® processor	Intel® 8 th Generation Core™ i5 or i7 quad-core processor	Intel® Core™ i5-8250U, Quad-Core, 1.6GHz (up to 3.4GHz) Intel® Core™ i7-8550U, Quad-Core, 1.8GHz (up to 4.0GHz)
RAM	4GB	8GB to 16GB	8GB to 16GB
Storage	128GB to 256GB Flash	128GB to 2TB Flash	128GB to 2TB Flash
Operating System	Microsoft® Windows® 7 Professional or Windows® 10 IoT Enterprise * Special order for Windows® 7 with Intel® 6 th Generation Core™ i processor	Microsoft® Windows® 10 IoT Enterprise	
Display	10.1" LED-backlight screen with capacitive multi-touch	10.1" high-brightness (800 nits) screen with capacitive touch, outdoor viewable	
Display Resolution	1920 x 1200	1920 x 1200	1920 x 1200
Control Switch and Buttons	1 power button, 3 programmable buttons, 1 RF switch		
Speaker	Built-in speaker	Built-in speaker	Built-in speaker
Network Interface			
WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band		
Bluetooth	Bluetooth 4.0 LE	Bluetooth 4.0 LE	Bluetooth 4.0 LE
I/O Ports			
USB Ports	1 (USB 3.0)	1 (USB 3.0)	USB 3.0 x 1 and USB Type-C x 1
Headset Jack	1 (3.5mm)	1 (3.5mm)	1 (3.5mm)
DC-in	1	1	1
Ethernet	N/A	N/A	Ethernet 10/ 100/ 1000MB Base-T LAN
Mechanical and Environmental			
AC/DC Adapter	Input: 100 – 240V AC; Output: 19V DC, 3.42A		
Battery Pack	Hot Swappable battery, 7.2V, 6150mAh	Hot swappable battery, 11.4V, 5400mAh; Hot swappable battery, 11.4V, 8000mAh (optional)	Hot swappable battery, 11.4V, 5400mAh; Hot swappable battery, 11.4V, 8000mAh (optional)
Enclosure	ABS + PC plastics and magnesium-aluminum alloy		
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm
Weight	3.1 lbs/ 1.4 kg	3.1 lbs/ 1.4 kg	3.1 lbs/ 1.4 kg
Regulatory	FCC Class B, CE, RoHS compliant		
Temperature	Operation**: -20°C to 60°C (-4°F to 140°F), tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II Storage: -55°C to 70°C (-67°F to 158°F)		Operation: -20°C – 60°C (AC mode), -20°C – 45°C (battery mode); Storage: -55°C – 70°C
Humidity	0% – 90% non-condensing		
Major Options			
Barcode Scanner	2D barcode scanner; reads 1D also		
Camera	2 megapixel front camera and 8 megapixel back camera with auto focus, white balance, gain control and exposure control		8 megapixel back camera; Or, Intel® RealSense™ Depth back camera, supports distance capture for the 3D scanning, environment sensing and background segmentation applications
Camera Light	N/A	N/A	External camera LED light with mounting bracket
Long Range Bluetooth	N/A	N/A	Class 1 Bluetooth (1000 ft)
GNSS Module	U-blox M8 GNSS module with concurrent reception of GPS and GLONASS; industry leading -167dBm navigation sensitivity		
Mobile Broadband	4G LTE/AWS	4G LTE/AWS	4G LTE/AWS

* Specifications subject to change without notice.

** For battery safety, optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F).

Accessories

