

IPC 1U-10255



IPC 1U-10255

The **IPC 1U-10255** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10255** provides the possibility to mount nine 2.5" and one 3.5" internal hard drives. Five standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 3.0 and USB 2.0 connectors and the universal ATX I/O plate complete this total package.



IPC 1U-10255

Motherboard	Mini ITX, mATX, μATX, ATX, SSI CEB
	maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6"
Orive Bays	5.25" external: 2*
	3.5" internal: 3*
	2.5" internal: 9*
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Internal: 5x 40mm
Cooling System	(5x included, Molex connector and hot pluggable)
Controls	Power-Button
	Reset-Button
_ED	Power
	HDD Activity
	3x Network Activity
	Alert
Power Supply	1U Server PSU, FLEX-ATX
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 27 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887101
EAN-Code	4260133126220
Scope of Delivery	4200133120220 Screw Set
scope of Benvery	Mounting bracket for FLEX-ATX PSU
- eatures	5x 40mm fan included
	USB 3.0 and USB 2.0 as block connector
	Universal ATX I/O plate

Dimensions and Weight

	Cage	Case	Package
Height	44.5mm	44.5mm	110mm
Width	433mm	482mm	555mm
Depth	550mm	578mm	730mm
	et): 6.90kg oss): 8.91k	g	

ower supply	<u></u>	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	_ 4 🗗
PCI-Express 6+2Pin	160	UL
PCI-Express Clin	tho	
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	_

1x Riser slot mounting direction

Certification: