

IPC 1U-10265



IPC 1U-10265

The **IPC 1U-10265** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10265** provides the possibility to mount nine 2.5" and three 3.5" internal hard drives. Five standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 2.0 connectors and the universal ATX I/O plate complete this total package.



IPC 1U-10265

<u>Specifications</u>	
Motherboard	Mini ITX, mATX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 340mm, 12" x 13.3"
Drive Bays	5.25" Slim-DVD: 1* 5.25" external: 2* 3.5" internal: 3* 2.5" internal: 9*
Front Connectors	USB 2.0: 2
Cooling System	Internal: 10x 40mm (5x included, Molex connector)
Controls	Power-Button Reset-Button
LED	Power
	HDD Activity
	3x Network Activity Alert
Power Supply	1U Server PSU, FLEX-ATX
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 27 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887102
EAN-Code	4260133126237
Scope of Delivery	Screw Set
Factorias	Mounting frame 5.25" to Slim-DVD/3.5"
Features	5x 40mm fan included USB 2.0 as block connector
	Universal ATX I/O plate
	1x Riser slot, screwless mounting, convertible for left and right
	mounting direction
	*can vary by using several mounting options

Dimensions and Weight

	Cage	Case	Package	
Height	44.5mm	44.5mm	110mm	
Width	433mm	482mm	555mm	
Depth	650mm	678mm	830mm	
Weight (net): 7.80kg Weight (gross): 10.41kg				

ower supply	<u></u>	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	◢.
P8 12V 8Pin	-	
PCI-Express 6+2Pin	1100	
PCI-Express 6 in	4NO	Ur
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification: