



## **IPC 2U-20240**

The **IPC 2U-20240** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-20240** provides the possibility to mount maximal eight 3.5" and three 2.5" internal hard drives. Two standard 80mm fans guarantee an optimal cooling.

The USB 3.0 & USB 2.0 connectors are easily reachable.

## Specifications

Motherboard	Mini ITX, Flex-ATX, mATX <sup>1</sup> , µATX <sup>1</sup> , ATX <sup>1</sup> maximal motherboard size WxD: 305mm x 191mm, 12" x 7.5" <small>(<sup>1</sup>maximal 191mm mounting depth)</small>
Drive Bays	5.25" external: 4* 3.5" internal: 8* 2.5" internal: 3*
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Internal: 2x 80mm <small>(included, 3pin (4pin connector))</small>
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	1U Server PSU <small>(maximal mounting depth 191mm)</small>
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 27 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887103
EAN-Code	4260133126244
Scope of Delivery	Screw Set Mounting bracket for 1U PSU Mounting rails for 3.5" hard drives
Features	2x 80mm fan included USB 3.0 and USB 2.0 as block connector 7x Low Profile slot with screwed and perforated slot brackets <small>*can vary by using several mounting options</small>

## Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	160mm
Width	433mm	482mm	555mm
Depth	400mm	438mm	560mm

Weight (net): 7.39kg  
Weight (gross): 9.10kg

## Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification:

