Inter-Tech Elektronik Handels GmbH

IPC 2098-SL



19" IPC 2098-SL 2U - Classic 19" Rack with a lot of space for different drives

You can remove the HDD cages with a few steps for easy mounting of internal devices.

On top you can mount an ATX PSU with 80mm fan to get a costefficient and professional solution.

Alternatively you can mount a 2U PSU.

The lockable doors in front of the slots prevent unauthorized access.

Integrated air filters ensure clean air and a flawless cooling.



IPC 2098-SL

Specifications

Motherboard Mini ITX, mATX, μATX, ATX maximal motherboard size WxD: 305mm x 290mm, 12" x 11.4" Max. Drive Bays 5.25" external: 1 3.5" external: 1* 3.5" internal: 5* 2.5" internal: 3* Front Connectors USB 2.0: Cooling System Front: 2x 60mm (optional) Inside: 4x 80mm (3x included, Molex connector, 1x optional) Power-Button Controls Reset-Button **LED** Power **HDD Activity** ATX PSU with 80mm fan, 2U PSU Power Supply Material 1.0-1.2mm Steel **Packing Units** Shipping Unit: 1 Piece Pallet: 20 Pieces Guarantee and Warranty Case 24 Months Warranty 88887127 Article Number EAN-Code 4260133128071 Scope of Delivery Keys, Screw Set Features Air filter Removable HDD cages 4x screwed Low Profile brackets Lockable front doors USB 2.0 internal as block connector *can vary by using several mounting options

Dimensions and Weight

	Cage	Case	Package
Height	87mm	89mm	175mm
Width	427mm	485mm	545mm
Depth	565mm	615mm	720mm
eight (net): eight (gross	8.72kg s): 10.80kg	9	

ower Supply	L	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	- 4
PCI-Express 6+2Pin	160	Ur
PCI-Express in	tn0	U ·
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification: