# Inter-Tech Elektronik Handels GmbH

## IPC 2U-2129N



#### **IPC 2U-2129N**

The **IPC 2U-2129N** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2129N** provides the possibility to mount a 1U or 2U server power supply at the rear of the chassis as well as a normal ATX power supply with 80mm fan in the front.

Furthermore the **IPC 2U-2129N** is equipped with four 80mm fans and perforated slot brackets for excellent cooling.

Both serial USB front connectors, one of them USB 3.0, round off the whole package.



## IPC 2U-2129N

#### **Specifications**

Motherboard	Mini ITV MATV HATV ATV SATV CCI EED
IIIaXIIIIuIII III	Mini ITX, mATX, µATX, ATX, eATX, SSI EEB otherboard size WxD: 305mm x 350mm, 12" x 13.8"
Drive Bays	5.25" external: 2
•	3.5" external: 6
	3.5" internal: 6
Front Connectors	USB 3.0: 1
	USB 2.0: 1
Cooling System	Internal: 4x 80mm
-	(assembled board 4x 3Pin to 1x Molex)
	Rear: 1x 60mm
Controls	(optional, not possible when using 2U/1U PSU)  Power-Button
Controls	Reset-Button
LED	Power
	HDD Activity
	3x Network Activity
	1x Alert
Power Supply	1U/2U Server PSU
. оно. очр.,	ATX PSU with 80mm fan
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece
<b>3</b>	Pallet: 18 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887194
EAN-Code	4260133128385
Scope of Delivery	Screw Set
. ,	Mounting frame for 2U / 1U PSU
Features	Serial 4x 80mm fan
	Possibility to mount a 1U/2U server PSU in the rear
	or a ATX PSU with 80mm fan in the front
	Removable and optional positionable HDD-cages
	5.25" drives screwless mountable
	Slot brackets screwed and perforated
	(Riser Slot rear wall optional (Item no. 88887160))

### **Dimensions and Weight**

		Cage	Case	Package
	Height	89mm	89mm	155mm
	Width	433mm	482mm	565mm
	Depth	650mm	680mm	825mm
We	ight (net):	8.93kg		

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	
PCI-Express 6+2Pin PCI-Express	ho	Ų٢
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm		_

Certification:

Weight (gross): 11.27kg