

IPC 3U-30240



IPC 3U-30240

The **IPC 3U-30240** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 3U-30240** provides the possibility to remove the two HDD cages on both sides and therefore to mount up to six 5.25" external hard drives. In the middle four external 3.5" HDDs are also available.

One 120mm and two 60mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 3.0 and USB 2.0 connectors and the lid with the snap locks complete this total package.



IPC 3U-30240

Specifications

Motherboard

maximal motherboard size WxD: $305 \text{mm} \times 191 \text{mm}$, $12" \times 7.5"$ (*maximal 191 mm mounting depth)

Drive Bays 5.25" external: 6* 3.5" internal: 12* 2.5" internal: 14*

Front Connectors

USB 3.0: 1
USB 2.0: 1

Cooling System Front: 1x 120mm

(included, Molex connector) 5.25" drive front bezel: 6x 40mm

Mini ITX, mATX, Flex-ATX, μATX¹, ATX¹

(optional) Rear: 2x 60mm

Controls (included, 3pin connector)
Power-Button
Reset-Button

LED Reset-Button
Power

HDD Activity 3x Network Activity

Alert Power Supply ATX PSU Material 1.0-1.2mm Steel

Packing Units
Shipping Unit: 1 Piece
Pallet: 24 Pieces

Guarantee and Warranty

Article Number

EAN-Code

Case 24 Months Warranty

88887106

4260133126275

Scope of Delivery Screw Set

Mounting rails for 3.5" hard drives
Features HDD cages removable and optional positionable

HDD cages removable and optional positionable Only 5 slot openings + 1 slot with optional Riser Card

1x 120mm and 2x 60mm fan included

USB 3.0 and USB 2.0 as block connector Lid with snap lock

*can vary by using several mounting option

Dimensions and Weight

	Cage	Case	Package		
Height	133.5mm	133.5mm	175mm		
Width	433mm	482mm	560mm		
Depth	400mm	438mm	560mm		
Weight (net): 8.65kg Weight (gross): 10.42kg					

Ρ	0	W	er	su	pp	ly

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	- 1 4
PCI-Express 6+2Pin	100	
PCI-Express Coin	hO	
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification: