

IPC 4088-S



19" IPC 4088-S 4U - Classic 19" Rack with a lot of space for different drives

You can remove the HDD cages with a few steps for easy mounting of internal devices.

You can mount 4 \times 2.5" Hard drives on a crossbeam inside the case. The crossbeam is also equipped with a slot card holder to ensure a safe usage.

The lockable doors in front of the slots prevent, unauthorized access.



IPC 4088-S

Specifications

Motherboard

Features

maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6" Max. Drive Bays 5.25" external: 3/21 3.5" external: 0/11 3.5" internal: 8 2.5" internal: 7* Front Connectors USB 2.0:

Cooling System Front: 1x 120mm (serial, Molex Connector)

Rear: 2x 80mm (optional)

Mini ITX, mATX, µATX, ATX

Power-Button Controls Reset-Button

LED Power **HDD Activity** ATX PSU, PS2 Mini-Redundant Power Supply

Material 1.0-1.2mm Steel Maximum CPU cooler height 130mm² Maximum graphics card length 275mm³

Shipping Unit: 1 Piece **Packing Units**

Pallet: 20 Pieces Case 24 Months Warranty Guarantee and Warranty Article Number 88887178

EAN-Code 4260133128101 Scope of Delivery Kevs

Screw Set

Mounting frame 5.25" to 3.5" external Removable HDD cages

7x screwed and perforated brackets

Slot Card holder each 1x for short, mid and high Slot Cards

Lockable front door

USB 2.0 internal as block connector

*max height 6x 9.5mm and 1x 15mm $^{\rm 1}$ by Using the mounting frame 5.25" to 3.5" external, one 5.25" is dropped $^{\rm 2}$ without middle bridge, $^{\rm 3}$ the amount of the internal 3.5" drives can vary

Dimensions and Weight

	Cage	Case	Package
Height	175mm	178mm	270mm
Width	427mm	485mm	550mm
Depth	448mm	483mm	590mm
	40.001		

Weight (net): 10.00kg Weight (gross): 12.10kg

Power Supply

	Connector	Quantity	Max. Length
	Mainboard 20+4Pin	-	-
	P4 12V 4Pin	-	-
	P4/EPS 4+4Pin	-	4.
	P8 12V 8Pin	-	
	PCI-Express 6+2Pin		
	PCI-Express in		-
	IDE 4Pin		-
	S-ATA	-	-
	Floppy	-	-
	RPM sensor cable	-	-
	Fan Control	-	-
	Fan: 120mm	-	-

Certification:

CE