



IPC 4U-4129-N

The 4U-4129-N is a rack in 4U format with a long installation depth (650mm). This offers you the option to install even large mainboards (eATX). Thanks to its robust design, the case provides ample space for disks (up to 11x 3.5" HDDs). Mounting rails for screw less installation of the internal 3.5" and external 5.25" drives are in the scope of delivery.

For an optimal cooling of your hardware, seven fans are preinstalled. In addition a dust filter, that can be removed for cleaning, is located behind the lockable front door and prevents both removable hdd cages from dust. Front USB ports, one USB 2.0 and one USB 3.0, complete the offer.

Specifications

| | |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motherboard | Mini ITX, µATX, ATX, eATX, SSI EEB maximum motherboard size BxT: 305mm x 345mm, 12" x 13.5" |
| Drive Bays | 5.25" external: 3* 3.5" internal: 11* 2.5" internal: 4* |
| Front Connectors | USB 3.0: 1 USB 2.0: 1 |
| Cooling System | Front: 2x 120mm (included, Molex connector) Internal: 3x 120mm (assembled board, 3x 3Pin to 1x Molex) Rear: 2x 80mm (included, 3pin connector) |
| Controls | Power-Button Reset-Button |
| LED | Power HDD Activity 3x Network Activity 1x Alert |
| Power Supply | ATX PSU |
| Material | 1.0-1.2mm Steel |
| Packing Units | Shipping Unit: 1 Piece Pallet: 12 Pieces |
| Guarantee and Warranty | Case 24 Months Warranty |
| Article Number | 88887206 |
| EAN-Code | 4260133129986 |
| Scope of Delivery | Keys Screw set Mounting frame for mini redundant power supply Wrench for assembly of the spacer Mounting rails for 5.25" and 3.5" drives |
| Features | Lockable front panel with dust filter cartridge Drive cages removable and selectively positionable Install 3.5" and 5.25" drives scewless Including 7 pre-installed fans in the front, rear and center bar USB 3.0 and USB 2.0 as block connector |

**the values may differ in certain combinations*

Dimensions and Weight

| | Cage | Case | Package |
|--------|-------|-------|---------|
| Height | 178mm | 178mm | 245mm |
| Width | 433mm | 482mm | 555mm |
| Depth | 650mm | 688mm | 835mm |

Weight (net): 13.94kg
Weight (gross): 16.60kg

Power Supply

| Connector | Quantity | Max. Length |
|-------------------|----------|-------------|
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | - |
| P8 12V 8Pin | - | - |
| PCI-Express 6+12 | - | - |
| PCI-Express 6 | - | - |
| IDE 4Pin | - | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan control | - | - |
| Fan 120mm | - | - |

Certification:

