Inter-Tech Elektronik Handels GmbH

ITX A80S Black



ITX A80S

The Mini-ITX case A80S by Inter-Tech - modern, stylish and strikingly practical. Completely made of aluminum, it also offers a perfect, thermal relief through various ventilation openings. Another practical feature is the external Slim-DVD slot, which offers you the option of installing an optical drive. Its simple design language also makes it look timelessly elegant.

Systems based on Mini-ITX can be designed very energy-saving, so that the standard, external 60W power supply is usually sufficient to run a powerful ITX computer. However, the internal Mini-ITX PSU board is able to handle input voltages of up to 120W.

- √ Robust full aluminum case
- ✓ 2x USB 3.0
- ✓including 60W power supply
- √ high quality feet, chrome plated



ITX A80S Black

Specifications

Motherboard ITX Slim-DVD: Drive bays

3.5" internal: 1/0* 2.5" internal: 0/1*

Front connectors USB 3.0: 2 Microphone:

Speaker: 2 Case openings WLAN antenna:

COM ports: 3 HDD tray: 2x 40x40x10mm Cooling system

or 50x50x10mm or 60x60x10mm

(laterally, optional) Power input For 12V plugs with dimensions of 5.5x2.5x10.7mm

Maximum CPU cooler height 40mm¹/30mm²

Maximum graphics card length

Packing units Shipping unit: 1 Piece Packing unit: 6 Pieces

Warranty 24 Months Article number 88881303 EAN-Code 4260455643405

External 60W Power Supply, 12V/5A Scope of delivery

Mini-ITX PSU max. 120W, 90°

Power cord

Cable ties Screw set

External 60W power supply **Features**

Mini-ITX PSU supports 12V power supplies up to 120W

Preparation for VESA mount 75x75mm Stands

* the values may differ for certain combinations

1 without drives, 2 with drives

Dimensions and Weight

	Cage	Case	Package	
Height	80mm	88mm	265mm	
Width	200mm	200mm	150mm	
Depth	200mm	200mm	240mm	
Weight (net): 1.19kg				

Weight (gross): 1.90kg

DC	/DC	board:	

Quantity	Max. Length
1x	-
1x	60cm
1x	20cm
1x	35cm
	1x 1x 1x

DC Output	Output Voltage (V)	Max. Output Current (A)
+3.30 V	+3.30	5.0
+5.00 V	+5.00	5.0
+5.00 VSB	+5.00	2.0
+12.00 V	+12.00	5.0
-12.00 V	-12.00	0.1

Certification:

CE