



JBC382F632(W)-6X00U-B

Fanless Embedded System



Specifications :

■ Dimension (W*H*D)	■ 185 * 142 * 60 mm
■ Construction	■ Aluminum housing
■ Colors	■ Black
■ Model Name	■ JBC382F632-6200U-B (i5-6200U) ■ JBC382F632-6300U-B (i5-6300U)
■ M/B model	■ JNF632-6200U ■ JNF632-6300U
■ CPU	■ Intel® Skylake-U(i5-6200U /i5-6300U), TDP: 15W
■ BIOS	■ AMI 128Mb Flash ROM
■ Memory	■ 2 * SO-DIMM DDR4 Slot (Max. 32GB)
■ Storage Space	■ 1 * 2.5" SATA Device ■ 1 * m-SATA SSD Device (Mini PCIe)
■ Front I/O Port	■ 2 * USB 2.0 ■ 2 * COM ■ 1 * MIC , 1 * Line out
■ Rear I/O Port	■ 2 * USB 2.0 , 4 * USB 3.0 ■ 1 * DP (max resolution:4096 x 2304@60Hz) ■ 1 * HDMI (max resolution:4096 x 2160@24Hz) ■ 2 * RJ45 (Intel Gigabit LAN) ■ 1 * Line out ■ WiFi (optional / JBC382F632W-6X00U-B)
■ Expansion Interface	■ Mini PCIe # 1 : Half-size (for mini PCIe module) ■ Mini PCIe # 2 : Full-size (shared with mSATA)
■ Power Source	■ Lockable 12V DC-in Jack ■ Adapter : AC_90~240V / DC_12V_5A / 60W

■ Certification	■ EMC : CE , FCC ■ Safety : RoHS , ErP
■ Environment	■ Operating Temperature : 0 ~ 50°C ■ Storage Temperature : -20 ~ 70°C
■ Mounting	■ Wall mounting Kits
■ Packing	■ Net Weight : 2.2KG ■ Gross Weight : 3.5KG ■ Color Box Dimension : 250(W) x 118 (D) x 295 (H) mm

External I/O :



Packing List :

Parts Number	Description	Set
G02-DVD22-A9-WF	Mini-ITX INTEL Skylake DVD 8.5G A9	1
G03-NF632-F	NF632 English Manual	1
G03-JC382QIG01-F	JC382 EN QIG	
L01AS037-F	Adapter 12V-5A-60W FSP060-DIBAN2	1
-----	Power cord	1
LCSCHBJC3XX-F	375 Screw Pack	2
HCS370MWM01B-2-F	JC370 Wall mount	2
HCS3XXDINRAILPS-F	DIN RAIL CLIP	2
G01-COM-H2M20-1F	CABLE COM CNN-2mm Head L=240mm K=10	2