



K-126L

The **K-126L** is the perfect rack for a small and cost-effective server system. Its compact design and its small installation depth of 250mm for ITX boards allows this case to fit into nearly every rack.

The **K-126L** provides internal space for optional 1x 3.5" or 2x 2.5" hard disks. Two serial 40mm fans, which are internally mounted behind the front panel, ensure a reliable and optimal cooling.

Further you can two USB 2.0 connectors in the front of the case next to the controls.

Specifications

| | |
|------------------------|---|
| Motherboard | ITX |
| Drive Bays | 5.25" external: 0 3.5" internal: 1 ¹ 2.5" internal: 2 ¹ |
| Front Connectors | USB 2.0: 2 |
| Cooling System | Internal: 2x 40mm (serial, Molex connector) |
| Controls | Power-Button Reset-Button |
| LED | Power HDD Activity |
| Material | 1.0-1.2mm Steel |
| Packing Units | Shipping Unit: 1 Piece Pallet: 45 Pieces |
| Guarantee and Warranty | Case 24 Months Warranty |
| Article Number | 88887000 |
| EAN-Code | 4260133129849 |
| Scope of Delivery | Screw Set Brackets for optional Flex-ATX PSU I/O Shield (Universal for cut out) |
| Features | Only 250mm Depth Serial 2x 40mm fan USB 2.0 intern as block connector <i>*Can vary by using different variations</i> |

Dimensions and Weight

| | Cage | Case | Package |
|--------|-------|-------|---------|
| Height | 45mm | 45mm | 150mm |
| Width | 430mm | 485mm | 390mm |
| Depth | 250mm | 285mm | 545mm |

Weight (net): 2.59kg
Weight (gross): 3.62kg

Power Supply

| Connector | Quantity | Max. Length |
|--------------------|----------|-------------|
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | - |
| P8 12V 8Pin | - | - |
| PCI-Express 6+2Pin | - | - |
| PCI-Express fan | - | - |
| IDE 4Pin | - | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan Control | - | - |
| Fan: 120mm | - | - |

Certification:

