



NVIDIA JETSON XAVIER NX 16GB

Xavier Performance. Nano Size.

The World's Smallest AI Supercomputer for Embedded and Edge Systems

NVIDIA® Jetson Xavier™ NX 16GB brings supercomputer performance to the edge in a compact system-on-module (SOM) that's smaller than a credit card. The energy-efficient Jetson Xavier NX module delivers server-class performance—up to 14 TOPS at 10W or 21 TOPS at 15W or 20W. This unique combination of form-factor, performance, and power advantage opens the door for innovative edge devices in manufacturing, logistics, retail, service, agriculture, smart cities, and medical instruments.

Pre-trained AI models from NVIDIA NGC, together with the NVIDIA TAO Toolkit, give you a faster path to trained and optimized AI networks. Seamless updates for your product are possible when you use Jetson cloud-native software capabilities to build, manage, and deploy your AI applications.

NVIDIA JetPack™ SDK enables multi-modal AI application development for Jetson Xavier NX 16GB with accelerated libraries supporting all major AI frameworks, as well as computer vision, computer graphics, multimedia, and more. Together with the latest NVIDIA tools for application development and optimization, JetPack ensures fast time to market and reduced development costs.

Jetson is designed for ease of development and speed of deployment, making it the most flexible and scalable platform to get to market and continuously update AI software over the lifetime of a product.

Key Features

Module

- > 384-core NVIDIA Volta™ GPU with 48 Tensor cores
- > 2x NVDLA
- > 6-core NVIDIA Carmel Arm®v8.2 64-bit CPU
- > 16GB 128-bit LPDDR4x
- > 16GB eMMC 5.1
- > 2x PVA

Power

- > Voltage input 5V
- > Module Power: 10W - 20W

NVIDIA JETSON XAVIER NX 16GB

TECHNICAL SPECIFICATIONS

AI Performance	21 TOPS (INT8)
GPU	NVIDIA Volta architecture with 384 NVIDIA CUDA® cores and 48 Tensor cores
Max GPU Freq	1.1GHz
CPU	6-core NVIDIA Carmel Arm®v8.2 64-bit CPU 6MB L2 + 4MB L3
CPU Max Freq	1.9GHz
DL Accelerator	2x NVDLA
Vision Accelerator	2x PVA
Memory	16GB 128-bit LPDDR4x 59.7 GB/s
Storage	16GB eMMC 5.1
CSI Camera	Up to 6 cameras (24 via virtual channels) 14 lanes (3x4 or 6x2 or 3x4 + 1x2 or 5x2 + 1x4) MIPI CSI-2 D-PHY 1.2 (up to 30 Gbps)
Video Encode	2x 4K60 4x 4K30 10x 1080p60 22x 1080p30 (H.265) 2x 4K60 4x 4K30 10x 1080p60 20x 1080p30 (H.264)
Video Decode	2x 8K30 6x 4K60 12x 4K30 22x 1080p60 44x 1080p30 (H.265) 2x 4K60 6x 4K30 10x 1080p60 22x 1080p30 (H.264)
PCIe	1 x1 (PCIe Gen3) + 1 x4 (PCIe Gen4)
USB	1x USB 3.1 (10 Gbps) 3x USB 2.0
Networking	10/100/1000 Base-T Ethernet
Display	2 multi-mode DP 1.4/eDP 1.4/HDMI 2.0
Other I/O	1x SDIO / 2x SPI / 3x UART / 2x I2S / 4x I2C / 1x CAN / GPIOs
Power	10W 15W 20W
Mechanical	45mm x 69.6mm 260-pin SO-DIMM connector

*Refer to the Software Features section of the latest NVIDIA Jetson Linux Developer Guide for a list of supported features

[Learn more](#)

Learn more at www.nvidia.com/Jetson

© 2021 NVIDIA Corporation. All rights reserved. NVIDIA, the NVIDIA logo, CUDA, Jetson, Jetson AGX Xavier, NVIDIA JetPack, and NVIDIA Volta are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated. ARM, AMBA and ARM Powered are registered trademarks of ARM Limited. Cortex, MPCore and Mali are trademarks of ARM Limited. All other brands or product names are the property of their respective holders. "ARM" is used to represent ARM Holdings plc; its operating company ARM Limited; and the regional subsidiaries ARM Inc.; ARM KK; ARM Korea Limited.; ARM Taiwan Limited; ARM France SAS; ARM Consulting (Shanghai) Co. Ltd.; ARM Germany GmbH; ARM Embedded Technologies Pvt. Ltd.; ARM Norway, AS and ARM Sweden AB. DEC21

