


7" IP65 HB Touch Monitor



- Comprehensive IP65 protection for applications under harsh circumstances, including water- and dustproof
- 1000+ cd/m² brightness for increased visibility even under direct sunlight
- Extended voltage input 8~36V
- All-in-One cable (VGA or HDMI)
- VESA 75 mounting
- 2 years guarantee



For industrial and outdoor applications in harsh environments, faytech provides IP65 High Brightness Touch Monitors, which are the perfect solution for such applications.


Advantages of these devices:

- Increased brightness (1000+ cd/m²)
- Complete IP65 protection (dust- and waterproof)
- All-in-one cable solution, with VGA or HDMI video connection, USB for Touch and a 8-36V power supply.

The case of the device consists of a robust, sealed aluminum enclosure, with on the front two buttons to adjust the brightness (with 5 available 5 levels). On the back of the device are fixation holes for either VESA 75 or VESA 100 mounting, which ensures solid fixation in any environment.

Available customizations:

- All-in-one cable, e.g. VGA, HDMI, Video, DVI, S-Video, Audio, Power supply, Voltage, USB or Serial for touch.
- Case color, logo's, housing and fixation
- Rail and/or VESA 75, VESA 100 on the back



Product name	7" IP65 High Brightness Touch Monitor
Article code / EAN number	FT07TMP65HB / 6920734007219 FT07TMP65HBHDMI / 6920734007226

IP Rating
IP65

LCD Panel	
Screen diagonal (Inch/cm)	7/17.78
Display active screen size (cm)	15.36×9.00
Aspect ratio	16:9
Physical resolution	1024×600
Maximum showable resolution	1920×1080
Colours displayed	262K
Brightness (cd/m²)	1000+
Contrast	700:1
Typical reaction time Tr/ Tf (ms)	10/15
Visual Angle horizontal/vertical (°)	150/145
Backlight / Backlight Lifetime (hours)	LED / 40,000

External Connectors	
All-In-One cable VGA version	1x VGA
	1x Video-In (RCA, AV)
	2x Audio-In (R/W)
	1x USB-Touch
	1x 8-36V DC-In
All-In-One cable HDMI version	1x HDMI
	1x USB-Touch
	1x 8-36V DC-In

Touch Panel	
Touch Technology	4-Wire Resistive
Touch Panel Drivers	Windows; Linux; Mac; Android
Touch Life (Contacts)	1 million in 1 location without failure
Surface Hardness	3H
Surface Treatment	Anti-glare

Operation / Mechanical	
Operating Temperature (°C)	-25 ~ +75
Humidity Range (RH)	10% - 90%
Net weight (kg)	1.10
Gross weight (kg)	2.10 (incl. cartontage)
Housing material	Aluminum
Housing (cm) L × W × H	21.40 × 13.40 × 3.85
Mounting	VESA 75

Power	
Power Indicator	Green LED
Power Supply	100-240V ACDC active switching; 12V DC-Out
Working Power (V)	8-36
Power Consumption (W)	10
Stand-By Consumption (W)	<1

Included in the Delivery	
Power Supply (see Power section)	
Driver DVD	
Short Installation Manual	
All-In-One cable (VGA or HDMI)	
Stylus	
Remote Controller	

