

12.5" faytech flat Touch Monitor

FT125FLATV2








- Full HD (1920 x 1080) LCD Panels
- Perfect touch monitor for people on-the-go
- 10-Finger-Multi Touch Capacitive Touch Panel
- Optically bonded Touch Panel to LCD Panel
- Thickness 5mm (screen) / 9.3mm (mainboard)
- Screen brightness buttons on the back
- Works with capacitive touch stylus (EETI touch)
- Weight of around 450 grams
- Plug and play ready



This **lightweight portable monitor**, also known as the **faytech flat**, is the perfect solution for people that require an extra screen while doing their day-to-day activities. Whether you connect it to your mobile phone, tablet or laptop, it will be an easy and convenient way of extending (or duplicating) the screen of your smart device over **USB Type-C** or **HDMI cable**.

With a weight of only **450-gram**, **12.5 inch** in size and **10-point multi-touch**, is this monitor a great tool for people on-the-go. Whether you are on a business trip, with the need to give presentations in different locations, a student constantly working on different projects or just a casual traveler that needs an extra screen, **faytech flat** is the solution for you.

Included with the device is a **flexible stand**, **USB Type-C cable** (1m) and **protection case**.



Product name	12.5" faytech flat Touch Monitor
Article code / EAN number	FT125FLATV2 / 6920734012558

IP Rating	
IP40	

LCD Panel	
Screen diagonal (Inch/cm)	12.5/31.75
Display active screen size (cm)	27.60×15.60
Aspect ratio	16:9
Physical resolution	1920×1080
Maximum showable resolution	1920×1200
Colours displayed	16.7M
Brightness (cd/m ²)	300
Contrast	700:1
Typical reaction time Tr/ Tf (ms)	14/11
Visual Angle horizontal/vertical (°)	178/178
Backlight / Backlight Lifetime (hours)	LED / min. 15,000

Included in the Delivery	
USB Type-C Cable	
Flexible 'Snake' Stand	
Protection Case	

Optional Accessories	
Capacitive Touch Stylus	

Touch Panel	
Touch Technology	Projected Capacitive 10-point Multitouch
Touch Panel Drivers	Windows; Linux; Mac; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Surface Treatment	Anti-glare (chemical etched)

Operation / Mechanical	
Operating Temperature (°C)	0 ~ +60
Humidity Range (RH)	20% - 80%
Net weight (kg)	0.45
Gross weight (kg)	1.20 (incl. cartonage)
Housing material	Black powdered aluminum
Housing (cm) L × W × H	28.95 × 21.20 × 0.93
Mounting	1/4-20 UNC screw thread

Power	
Working Power (V)	5-24
Power Consumption (W)	5
Stand-By Consumption (W)	0.5

External Connectors	
1x HDMI	
1x USB Type-C - for Signal / Power	
1x USB Type-C - for Power	
1x PC-Audio	

