

Nothing But LEDs is the leader in cutting-edge refrigerated display lighting technology! Our new LED cooler light produces wider beam for more evenly dispersed lighting. Also our LED cooler lights have a built-in driver that allows it to be installed in minutes. Our newest LED Cooler light and Freezer Lamps deliver crisp, bright light that creates attractive food and product displays in freezers and walk-in refrigerator cases. They consume less energy and run longer and cooler than fluorescent freezer bulbs, lowering operating costs and reducing the risk of food spoilage.

Product Features

- Up to 130 lumens per watt
- IP65 Rated
- CRI >80
- Easy Daisy Chain Installation
- Remarkable improvement of the appearance of food or commodity being displayed
- Noticeable cost savings by up to 75% due to the energy-efficient design

- Instant activation in cold environment
- Flexible lengths for both vertical and horizontal installation such as 5ft
- Built-in driver
- Mercury and lead free
- Input Voltage 100-277V
- UL & DLC Listed
- 5 Year warranty



SKU #	Model #	Watt	Lumens	ССТ	Length	Input Voltage	IP	Certifications
1560729	ZY-22W1500 BINS (5700K)	22W	2860Lm	5700K	5ft	100-277V	IP65	UL & DLC


SKU 1560729

Specifications

Parameter	Description	Value
	Model #	ZY-22W1500 BINS(5700K)
	Watt	22W
General	Color Temperature Adj.	5700К
Performance	Lumens	2860Lm
	Lumen Efficacy	Up to 130LM/W
	CRI (Ra)	≥80
	Beam Angle	145.4° Degree
	Input Voltage	100-277V
Plantstaal	Frequency	60Hz
Electrical	PF	≥0.9
	THD	<22%
	Driver Brand	NBL
	Operating Temperature	-25°C - 20°C
	Storage Temperature	-25°C - 50°C
	Operating Humidity	65% RH
Physical	Lens	Clear
	LED Brand	Venas
	LED Type	SMD2835
	Housing	Aluminum
	Housing Color	White
Qualification	IP	IP65
	Warranty	5 Year




Correlated Color Temperature (CCT)







Photometric Data



Illuminance at a Distance						
	Center Beam fc	Beam Width				
17.0 R	2.28 fc 🔪	46.2 ft				
34.0R	0.57 fc	92.3 ft				
51.0R	0.25 fc	138.5 ft				
68.0R	0.14 fc	184.6 ft				
85.0ft	0.09 fc	230.8 ft				
102.0ft	0.06 fc	276.9 ft				
Beam Spread: 107.2°						







Easy Daisy-Chain Installation






Installation and Electrical Connection




<u>WARNING</u>


RISK OF FIRE, ELECTRIC SHOCK OR PERSONAL INJURY Before installation, turn power off.




1. Position and fix the lamps.



2. Connect the male and female waterproof interfaces.



3. Tighten the nut of the connector.



4. Use diagonal pliers to cut any one of the wires at the head and tail close to the water head end, peel the wire core and connect it with the mains power input end.

Tolls Required









Packaging

SKU #	Size (Inches)	Qty / Box	Net Weight	Gross Weight
1560729	61.02 x 8.26 x 9.05	25 Pcs /Box	31LBS	33LBS

Application Image



Warranty

5 Years Warranty



Application Image

