

LED LINKABLE FIXTURES



Linkable T8 LED Integrated Lamps to perform efficiently in conditions where low voltage, halogen, or fluorescent luminaires have traditionally been used. Our LED tubes incorporate integral drivers, are self-supporting and can be surface mounted. Individual units can be plugged together for continuous lengths up to 200W. Our Lamps connect directly to line voltage and can be used in any interior space.

Product Features

Efficacy up to 140 Lumens per watt
Input Voltage 100-277Vac 50-60Hz
Operates directly from line voltage
Usable as a stand alone fixture

Linkable up to 200W at AC120V
Aluminum and PC housing
ETL & DLC Listed
5 Year warranty

LED LINKABLE FIXTURES



SKU #	Model #	Watt	Lumens	CCT	Size	Lens	Certifications
1510717	BLT-T8-30P4FT-INT26500K-C	30W	4200Lm	6500K	4ft	Clear	ETL
1530837	BLT-T8-30P4FT-INT2(4000K)-F	30W	4200Lm	4000K	4ft	Frosted	ETL
1510623	BLT-T8-60P8FT-INT26500K-F	60W	8400Lm	6500K	8ft	Frosted	ETL
1530547	BLT-T8-60P8FT-INT2(5000K)-F	60W	8400Lm	5000K	8ft	Frosted	DLC
1510715	BLT-T8-60P8FT-INT26500K-C	60W	8400Lm	6500K	8ft	Clear	ETL
1510624	BLT-T8-60P8FT-INT26500K-S	60W	8400Lm	6500K	8ft	Striped	ETL
1530838	BLT-T8-60P8FT-INT2(4000K)-F	60W	8400Lm	4000K	8ft	Frosted	ETL
1520574	BLT-T8-90P8FT-INT4(5000K)-C	90W	12600Lm	5000K	8ft	Clear	ETL
1560700	BLT-T8-90P8FT-INT4(5000K)-C	90W	12600Lm	6500K	8ft	Clear	ETL

LED LINKABLE FIXTURES

SKU #	Model #	Watt	Lumens	CCT	Size	Lens	Dimming	Input Voltage	Certifications
1560744	BLT-T8-30P4FT-INT26500K-S	30W	4200Lm	6500K	4FT	Striped	Triac Dimmable	100-277Vac	ETL & DLC
1560745	BLT-T8-30P4FT-INT25000K-F	30W	4200Lm	5000K	4FT	Frosted	Triac Dimmable	100-277Vac	ETL & DLC

LED LINKABLE FIXTURES

SKU: 1560744

Specifications

Parameter	Description	Value
General Performance	Wattage	30W
	Lumen	4200Lm
	Lumen Efficacy	Up to 140LM/W
	Color Temperature	6500K
	CRI (Ra)	>80
	Dimming	Triac Dimmable
	Beam Angle	100° Degree
	Diffuser Type	Striped
Electrical	Input Voltage	100-277Vac
	Frequency	50/60Hz
	Power Factor	>0.95
Physical	Operating Temperature	-30°C to 65°C
	Operating Humidity	N/A
	Storage Temperature	N/A
	LED Type	SMC2835
	Housing Material	Aluminum + PC Cover
Qualification	Housing Color	White
	IP Rating	IP22
	Warranty	5 Year

LED LINKABLE FIXTURES



SKU: 1560745

Specifications

Parameter	Description	Value
General Performance	Wattage	30W
	Lumen	4200Lm
	Lumen Efficacy	Up to 140LM/W
	Color Temperature	5000K
	CRI (Ra)	>80
	Dimming	Triac Dimmable
	Beam Angle	100° Degree
	Diffuser Type	Frosted
Electrical	Input Voltage	100-277Vac
	Frequency	50/60Hz
	Power Factor	>0.95
Physical	Operating Temperature	-30°C to 65°C
	Operating Humidity	N/A
	Storage Temperature	N/A
	LED Type	SMC2835
	Housing Material	Aluminum + PC Cover
Qualification	Housing Color	White
	IP Rating	IP22
	Warranty	5 Year

LED LINKABLE FIXTURES

Specifications

Parameter	Description	Value
General Performance	Wattage	30W
	Lumen	4200Lm
	Lumen Efficacy	Up to 140LM/W
	Color Temperature	6500K 5000K 4000K
	CRI (Ra)	>80
	Beam Angle	100° Degree
	Diffuser Type	Striped / Clear / Frosted
Electrical	Input Voltage	100-277Vac
	Frequency	50/60Hz
	Power Factor	>0.95
Physical	Operating Temperature	-30°C to 65°C
	Operating Humidity	N/A
	Storage Temperature	N/A
	LED Type	SMC2835
	Housing Material	Aluminum + PC Cover
Qualification	Housing Color	White
	IP Rating	IP22
	Warranty	5 Year

