




Technical Sheet

Product

MOUNTED FLAP WHEELS Aluminum oxide

1. Description of Product

Dimensions(in):	1 1/2" x 1" x 1/4"
Grit:	40
Abrasive:	ALUMINUM OXIDE
Part Number:	FW-112040
Max RPM:	25,000



1. Application

- Premium aluminum oxide cloth for deburring, cleaning and finishing of flat or uneven surfaces
- For use on steel, non-ferrous metals, wood, stainless steel, cast iron, plastics etc.

2. Operating instructions

- Use the proper machine
- Insert the flap wheel into the tool as deep as it will go before securing
- Tool should be running at full speed before engaging too with material
- Do not use excessive pressure
- Excessive pressure can cause tearing or cloth backing
- Excessive pressure or hitting increases the chance of resin failure

3. Handling

- Handle with care to prevent failure and tearing of abrasive flaps
- Inspect all products prior to use, if product appears to be faulty or broken do not use

4. Safety information

- Never exceed speed marked in catalog
- Fully PPE Safety equipment suggested (gloves, hearing protection, respiratory protection, safety glasses)
- Improper use can cause severe injury
- Check that the tool is secured and that there is no vibration or play in the tool before starting

5. Storage

- Store flap wheels in their original packaging
- Humidity and moisture can lead to rusting of the steel shank

6. Packaging units

- Box Quantity: 10
- Case Quantity: 200



1021 N. Fuller St, Santa Ana, CA 92701
TEL 949.250.9060 FAX 949.250.8711

CALL TO PLACE ORDER
1.855.817.8390

www.continentalabrasives.com