

POCKET COLLECTION

SPECIFICATIONS

- 120-277V INPUT VOLTAGE, 50/60Hz
- CONSTANT CURRENT AT 700 MILLIAMPS
- CLASS 2 DRIVER POWER FACTOR >.9
- OPERATING TEMPERATURE -18°C (0°F) TO 40°C (104°F) (25°C NOMINAL)
- ESTIMATED 50,000 HRS L₇₀*
- THERMALLY PROTECTED LED ARRAY
- FITTER NECK ACRYLIC DIFFUSER
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT PLASTICS
- UL/CUL LISTED FOR WET LOCATION
- STANDARD PACK QTY: 6



SPJ109


SPJ123

SPJ106


SPJ103




EXTENDS: 5 3/4"
HCMT: 2 3/8"




EXTENDS: 6 1/2"
HCMT: 2 3/8"



EXTENDS: 5 3/4"
HCMT: 2 3/8"



EXTENDS: 7"
HCMT: 4 1/4"



EXAMPLE # **SPJ103-L900C-BW**

STYLE #	SOURCE/WATTAGE	COLOR TEMP	BODY	DIFFUSER
SPJ103 = HARBOR	L900C = 4 CREE LED ARRAY (10W) 11.3W POWER INPUT 912 LUMENS 80 LUMENS PER WATT**	4000K CRI = 74 (TYP)	B = BLACK W = WHITE	W = WHITE
SPJ106 = GLOBE				
SPJ109 = LONG BEACH				
SPJ123 = ACORN				

L900C LED REPLACEMENT PARTS
L09C-DC-700-04-R = 4 CREE LED ARRAY
IG900-DMV-1 = LED DRIVER

* DATA PER LM80/TM21 @ 1000MA AVAILABLE UPON REQUEST

** ESTIMATED FOR LED SOURCE

For more information regarding SPJ Lighting's LED Fixtures and Custom Packaging please contact our sales department at **800-469-3637** or visit www.spjlighting.com.com

Specifications, design & components subject to change without notice. Printed in U.S.A. © 2012 SPJ Lighting Inc.

