


CENTURY COLLECTION

SPECIFICATIONS


- 120-277V INPUT VOLTAGE, 50/60Hz
- CONSTANT CURRENT AT 700 MILLIAMPS
- DRIVER UL CLASS 2, POWER FACTOR > .90
- OPERATING TEMPERATURE -18°C (0°F) TO 40°C (104°F) (25°C NOMINAL)
- ESTIMATED 50,000 HRS L₇₀*
- THERMALLY PROTECTED LED ARRAY
- ACRYLIC DIFFUSER & ALUMINUM BASE
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT PLASTICS
- UL/CUL LISTED FOR DAMP LOCATION
- STANDARD PACK QTY: 6



SPJ321



SPJ322



EXAMPLE # **SPJ321-L900C-BF**

STYLE #	SOURCE/WATTAGE	COLOR TEMP	BODY	DIFFUSER	OPTION
SPJ321 = 8.25"	L900C = 4 CREE LED ARRAY 11.3W POWER INPUT 912 LUMENS 80 LUMENS PER WATT**	4000K CRI = 74 (TYP)	B = BLACK W = WHITE	F = FROSTED	P = PHOTOCELL Photocells are only available for 120V applications
SPJ322 = 10.25"	L1800C = 8 CREE LED ARRAY (18W) 22W POWER INPUT 1824 LUMENS 82 LUMENS PER WATT**				

L900C LED REPLACEMENT PARTS
L09C-DC-700-04-R = 4 CREE LED ARRAY
IG900-DMV-1 = LED DRIVER

L1800C LED REPLACEMENT PARTS
L18C-DC-700-08-R = 8 CREE LED ARRAY
IG1800-DMV-1 = LED DRIVER

* DATA PER LM80/TM21 @ 1000MA AVAILABLE UPON REQUEST

** ESTIMATED FOR LED SOURCE

For more information regarding SPJ Lighting's LED Fixtures and Custom Packaging please contact our sales department at **800-469-3637** or visit **www.spjlighting.com.com**



Specifications, design & components subject to change without notice. Printed in U.S.A. © 2012 SPJ Lighting Inc.

1203.1